

APOLLO

Industrial Luminaires



This industrial luminaire has a 120-degree lighting angle. The LED hall spotlight is equipped with high-tech lenses that prevent glare and offers stable performance with a low UGR value. Made from IP65 waterproof aluminum casting material, the luminaire can be used safely even on rainy days. The luminaire is ideal for wide lighting areas such as garages, warehouses, greenhouses, and factories. It is also suitable for places like gyms, logistics centers, toll booths, and supermarkets. This luminaire provides a safe and long-lasting lighting solution for both indoor and outdoor environments.



RAL COLORS

Std.

9005

Opt.

9016

9006

APL40

IP66  

Code	Beam Angle	Luminous Flux	System Power	Weight
APL40-L 150	80°	19.350 lm	150 W	4.7 Kg
APL40 -L 170	80°	21.950 lm	170 W	4.7 Kg
APL40-L 200	80°	25.820 lm	200 W	4.7 Kg
APL40-L 230	80°	32.050 lm	250 W	4.7 Kg
APL40-C - 150	115°	20.070 lm	150 W	5 Kg
APL40-C - 170	115°	22.770 lm	170 W	5 Kg
APL40-C - 200	115°	26.785 lm	200 W	5 Kg
APL40-C - 230	115°	33.250 lm	250 W	5 Kg

Body: Aluminum injection

Diffuser: PMMA lens (only APL model)

Front Glass: 5mm thick tempered glass
(only APL-C model)

Voltage: 220~240 VAC

Driver: Included

Color Temperature: 3000-4000-5000-6500K

Led: Mid Power

ACCESSORIES
Circular Reflector




Body: Sheet Metal


BRACKETS



Free Bracket



386mm



386mm




386mm




BOX DIMENSIONS
20x40x40cm



BOX WEIGHT
5.5 kg



cd/klm
— C0 - C180 — C90 - C270



cd/klm
— C0 - C180 — C90 - C270



RAL COLORS

Std.



Opt.



APL30/L

IP66


Code	Luminous Flux	System Power	Weight
APL30/L150	23.550 lm	150 W	2.2 Kg
APL30/L180	26.450 lm	180 W	2.2 Kg

Body: Aluminum injection
Diffuser: PMMA lens


Voltage: 220~240 VAC
Driver: Included

Color Temperature: 3000-4000-5000-6500K
Led: Mid Power

BRACKETS



Free Bracket



Ø 285mm



150mm


Ø 285mm



BOX DIMENSIONS
30x30x16xcm



BOX WEIGHT
2.5 kg





RAL COLORS

Std.  9005

Opt.  9016

 9006

APL20/L

IP66  

Code	Luminous Flux	System Power	Weight
APL20/L 80	12.650 lm	80 W	1.6 Kg
APL20/L 100	15.500 lm	100 W	1.6 Kg
APL20/L 120	17.900 lm	120 W	1.6 Kg

Body: Aluminum injection
Diffuser: PMMA lens


Voltage: 220~240 VAC
Driver: Included

Color Temperature: 3000-4000-5000-6500K
Led: Mid Power

BRACKETS



Free Bracket




BOX DIMENSIONS
25x25x16xcm


BOX WEIGHT
1.8 kg

