



OFISLED

Recessed Luminaires

OFISLED has been developed to bring advanced LED technology into office lighting. It can be produced for all types of suspended ceilings, with manufacturing customized according to the brand and model of the ceiling system to be used.

In the optical design of the fixture, glare and screen reflections—the most critical factors in office environments—have been carefully considered, and Cat-1 and Cat-2 types have been developed accordingly.



RAL COLORS

Std.

9016

Opt.

9005

9006

LGS

IP20  

Code	Luminous Flux	System Power	Weight
LGS60-60/3	3.000 lm	27 W	5 Kg
LGS60-60/4	3.900 lm	35 W	5 Kg
LGS30-120/2	5.200 lm	52 W	5.5 Kg

Body: 0.6mm thick DKP sheet steel

Reflector: Alanod Miro Silver Aluminum

Diffuser: 2.8 mm thick microprismatic lens

Optic: Cat1, Cat2

Voltage: 220~240 VAC

Driver: Included

Color Temperature: 2700-3000-4000-5000-6500K

Led: Mid Power



LGS/2

LGS/3


LGS/4

Optics



Prismatic

Opal



	Code	a	b	Cut-Out
GYPSUM	LGS001 30-60	295 mm	595 mm	280x580 mm
	LGS001 60-60	595 mm	595 mm	580x580 mm
	LGS001 30-120	295 mm	1195 mm	280x1180 mm
CLIP-IN	LGS002 30-60	299 mm	599 mm	-
	LGS002 60-60	599 mm	599 mm	-
	LGS002 30-120	299 mm	1199 mm	-
MODULAR	LGS300 30-60	295 mm	595 mm	-
	LGS300 60-60	595 mm	595 mm	-
	LGS300 30-120	295 mm	1195 mm	-



BOX DIMENSIONS

LGS 60-60 67x61x9cm
LGS 30-120 32x122x9cm



BOX WEIGHT

5.5 kg
6 kg

