

RLM/RV

Surface Mounted Downlight



RLM/RV is a spotlight developed for surface-mounted uses. It possesses all the optical features of the RLM series. There is a space at the base of the spotlight for easy ceiling mounting. Although it is surface-mounted, it allows light to be directed in all directions and at all angle.



RAL COLORS

Std.

9016

Opt.

9005

9006

RLM/R^Y

IP20  

Code	Beam Angle	Luminous Flux	System Power	Weight
RLM/R ^Y 10 NB	15°	1.180 lm	10 W	0.60 Kg
RLM/R ^Y 10 MB	40°	1.115 lm	10 W	0.60 Kg
RLM/R ^Y 10 WB	60°	1.130 lm	10 W	0.60 Kg
RLM/R ^Y 20 NB	15°	2.090 lm	20 W	0.60 Kg
RLM/R ^Y 20 MB	40°	1.970 lm	20 W	0.60 Kg
RLM/R ^Y 20 WB	60°	2.005 lm	20 W	0.60 Kg
RLM/R ^Y 30 NB	15°	2.995 lm	30 W	0.60 Kg
RLM/R ^Y 30MB	40°	2.825 lm	30 W	0.60 Kg
RLM/R ^Y 30 WB	60°	2.880 lm	30 W	0.60 Kg

Body: Aluminum
Reflector: PC

Driver: Included
Voltage: 220~240 VAC

Color Temperature: 2700-3000-4000-5000-6500K
Led: COB


GOLD REFLECTOR



ACCESSORY




Honeycomb Louvre




BOX DIMENSIONS
27x18x17 cm



BOX WEIGHT
0.8 Kg

NARROW




cd/klm
— CO - C180 — C90 - C270

MEDIUM



cd/klm
— CO - C180 — C90 - C270

WIDE



cd/klm
— CO - C180 — C90 - C270