



RLP/S

Surface Mounted Downlight

RLP/S is designed to suit the needs of hanging fittings or surface mounted fixtures. Its elegant and proportional style combine with high performance and safety aspects. New generation high performance COB LEDs furnish extremely good fixture efficiency and stable operation by virtue of high-efficient reflectors.



RAL COLORS

Std.

9016

Opt.

9005

9006

RLP/S

IP20  

Code	Beam Angle	Luminous Flux	System Power	Weight
RLP/S NB	24°	1.050 lm	10 W	0.6 Kg
RLP/S MB	40°	1.000 lm	10 W	0.6 Kg
RLP/S WB	60°	1.020 lm	10 W	0.6 Kg
RLP/S NB	24°	1.400 lm	15 W	0.6 Kg
RLP/S MB	40°	1.350 lm	15 W	0.6 Kg
RLP/S WB	60°	1.380 lm	15 W	0.6 Kg
RLP/SM NB	24°	1.050 lm	10 W	0.76 Kg
RLP/SM MB	40°	1.000 lm	10 W	0.76 Kg
RLP/SM WB	60°	1.020 lm	10 W	0.76 Kg
RLP/SM NB	24°	1.400 lm	15 W	0.76 Kg
RLP/SM MB	40°	1.350 lm	15 W	0.76 Kg
RLP/SM WB	60°	1.380 lm	15 W	0.76 Kg

Body: Aluminum
Reflector: PC
Front Glass: 3mm thick tempered glass

Driver: Included
Voltage: 220~240 VAC

Color Temperature: 2700-3000-4000-5000-6500K
Led: COB

ACCESSORY



Honeycomb Louvre




BOX DIMENSIONS
 RLP/S 36x36x13 cm
 RLP/SM 36x36x13 cm




BOX WEIGHT
 RLP/S 0.8kg
 RLP/SM 1 kg

NARROW




cd/klm
 — CO - C180 — C90 - C270

MEDIUM



cd/klm
 — CO - C180 — C90 - C270

WIDE



cd/klm
 — CO - C180 — C90 - C270