











LITPA Lighting was founded in 1992 with the sole intention of ensuring the manufacture and direct marketing of quality lighting solutions through its extensive and quality range of lighting fixtures. Our mission is to provide lighting solutions for indoor and outdoor settings that are not only reasonably priced, but due to our high-quality engineering and extensive research veritably “light-up your lives”.

LITPA seeks to provide not only suitable materials for use in its production, but also to ensure that it meets the lighting needs of the space in which it will be situated. For this reason, material quality that will meet the relevant lighting criteria alone is not enough. We also seek to fulfill the following criteria for our lighting solutions; that our fixtures must ensure viewing optimization, enhance and optimize the aesthetic value of the area in which fixtures are to be placed, ensure ease of mounting, wear-resistance appropriate to the conditions, suitability to the electrical supply; while also providing lighting comfort of the space to users, easy maintenance and economical usage. All of these considerations have been made in advance for you by our advanced and highly dedicated staff.










Our meticulous quality-control and attention to detail at every stage of the manufacturing process is of the utmost importance in our adherence to global standards. Every item, from the materials we use for products that we produce is checked to ensure the highest specifications of quality and performance.

Our company has placed a great deal of importance to its R&D (Research and Development) also, hence our dedicated, experienced and energetic team of professionals seeks always to surpass itself in provision of product and service delivery to our clients. With one call, we seek to be as close as possible to our clients – wherever they are and no matter where our offices are. LITPA's progressive approach, values and guidelines has led to success with Turkey 's global corporations and business.

## OUTDOOR

STREET LIGHTING 4 - 7		FLOODLIGHT 8 - 11		WALLWASHER & LINEAR 12- 15	
	GROUND RECESSED 16 - 17		GARDEN LIGHTING 18- 20		WALL LUMINAIRES 21
CANOPY LUMINAIRES 22		TUNNEL LIGHTING 23			

## INDOOR

DOWNLIGHT 26 - 39		SURFACE MOUNTED 40 - 41		OFFICE LIGHTING 42 - 55	
	HYGIENIC ROOM 56 - 57		LINEAR 58 - 65		DECORATIVE 66 - 67
WALL LUMINAIRES 68 - 71		INDUSTRIAL & WEATHERPROOF 72 - 78		LINEAR for RETAILERS 80 - 83	



# OUTDOOR LIGHTING

## LUMINAIRES







## Street Lighting


# STREETRAY

IP66


Stretray is a highly efficient IP66 protection class road lighting fixture which using LED technology. Our fixtures are produced in four different types. STREETRAY road fixtures can be used in all areas of road lighting including M1 motorways, urban street lighting and lighting of alleys. Its monolithic integrally cooled die-cast aluminum body structure extends the life of light source and reduces maintenance costs. Stretray also offers many features such as angle adjustable mounting bracket, channel water management and protective cover which can optionally be installed. The fixture's body is designed to be suitable for all kinds of urban automation. Automation systems which can be used in Wi-Fi, Zigbee, RF, PLC, Dali, KNX systems are also available upon request.




LYS 100




LYS 50



LYS 20




LYS 15



LYS 24V/DC Optional Solar System


Code	LYS 100 (Maxi)	LYS 50 (Midi)	LYS 20 (Mini)	LYS 15 (Micro)	LYS 20/DC (Solar)
LED	High Efficiency Power LED				
System Power	170 W 200 W 250 W 300 W	80 W 110 W 150 W	45 W 72 W	20 W 27 W 35 W	30 W 40 W 50 W
Light Flux	21,000 lm 26,000 lm 30,720 lm 35,690 lm	10,150 lm 13,200 lm 17,250 lm	5,200 lm 7,500 lm	2,080 lm 3,000 lm 4,000 lm	3,630 lm 4,840 lm 6,050 lm
Colour Temperature	4000 - 5000 - 6500 K				
Voltage	220V - 50Hz				24 VDC
Body	Aluminum injection				
Optic	High-efficiency lens				
Cooler	Cooling from the surface of the aluminum body				
Glass	5 mm thick tempered and serigraphy printed				
Accessory	Anti-corrosive cover (only LYS50-LYS100)				
Colour	Grey				
Box Dimensions	102x40x12cm	78x33x13cm	60x27x12cm	60x27x10cm	60x27x12cm
Weight	15.200 gr	9.800 gr	5.700 gr	4.800 gr	5.700 gr



## Pedestrian Areas & Walkways

### RINGA

### IP65



RNY4







RNY/T4 AGORA



RNY2



RNY OP



Ringa, which in particular is preferred in parks, gardens, walking trails and residential areas, has been designed with the purpose of bringing diversity to the external environment thanks to the aesthetic design thereof. The aluminum body is manufactured according to protection class IP65 to be resistant to outdoor conditions. Usage height is on 4 to 6 meters high pole while way of mounting is on the top of a Ø60mm pole.

Highly efficient LEDs have been used and optimum drive currents have been preferred in Ringa fixtures in order to save energy. Ringa, designed to prevent light from escaping into the sky, has been designed also to prevent light pollution by virtue of this feature.


Code	RNY2/40 RNY2/70	RNY4/80 RNY4/140	RNY/T4/250 RNY/T4/300
LED	High Efficiency Power LED		
System Power	40W 70W	80W 140W	250W 300W
Light Flux	3500 lm 6500 lm	7300 lm 12670 lm	25900 lm 28900 lm
Colour Temperature	3000 - 4000 - 5000 - 5700 - 6500 K		
Voltage	220V - 50Hz		
Body	Aluminum injection painted with electrostatic paint		
Cooler	Cooling from the surface of the aluminum body		
Optic	High Efficiency lenses; 21°- 26°- 45°- 65°- (21°+37°) or reflectors; 21°- 30°- 63°- 90°		
Glass	Clear glass, serigraphy printed		
Accessory	Apparatus for pole mounting		
Colour	Grey or RAL Color		
Box Dimensions	70x65x35 cm	70x65x70 cm	70x65x70 cm
Weight	9.800 gr	12.800 gr	12.800 gr

## Pedestrian Areas &amp; Walkways

## CAIRO

IP66





These are designed to be cornered and integrated with the body except for the usual. In the design of luminaires, emphasis was placed on modern and aesthetic elements as much as light efficiency. Thanks to the LED module structures, luminaire powers can be adjusted to desired levels. High efficiency LEDs and optical structures provide the desired light levels and distributions.



CRA/L



CRA/Y




Code	CRA/L	CRA/Y
LED	High Efficiency Power LEDs	
System Power	1x50W	
Light Flux	5000lm	
Colour Temperature	4000 - 5000 - 6500 K	
Voltage	220V - 50Hz	
Body	Aluminum extrusion body, DKP sheet base thick 10mm	
Cooler	Cooling from the surface of the body	
Colour	Grey	

## Pedestrian Areas & Walkways





### CAIRO

IP66



CRAV

Cairo; With its simple and elegant profile structure in lighting, it reflects a contemporary and innovative understanding style. Thanks to its pole structure and design, it has an aesthetic appearance in many areas. The luminaires are offered with different wattage options. Poles from 3.5 meters to 8 meters can be used. The models produced in double arm structure can meet the light requirements in both different directions.



Code	CRAV2	CRAV1
LED	High Efficiency Power LEDs	
System Power	4x50W	2x50W
Light Flux	20.000lm	10.000lm
Colour Temperature	4000 - 5000 - 6500 K	
Voltage	220V - 50Hz	
Body	Aluminum extrusion body, DKP sheet base thick 10mm	
Cooler	Cooling from the surface of the body	
Colour	Grey	




## Floodlights

## HERCULED

IP66





HCL/PRO





HCL/B

BASIC

Herculed projectors are made for outdoor use. They can also be used as white, red, green, blue, yellow or RGB. With Litpa's exclusive DMX system, it is possible to open and close many luminaires from a single point, to dim, to manage different scenarios. Litpa uses light fittings that are fully compatible with the LED structure in these luminaires, allowing the light to reach only the desired area without loss.

Adjustable  
angle

DMX Controller




Code	HCL/PRO	HCL/B
LED	High Efficiency Multi-Power	High Efficiency Power Led
System Power	65 W 130 W 210 W	180 W 240 W
Light Flux	RGBW	18.300 lm 24.000 lm
Color Temperature	RGBW	3000 - 4000 5000K R-G-B-A
Voltage	220V - 50Hz	
Body	Aluminum injection	
Diffuser	Tempered glass	
Optic	9° - 28°- (42°+30°) High efficiency	12° - 25°- 61° High efficiency lens
Box Dimensions	44x48x19cm	44x48x19cm
Weight	12.000 gr	12.000 gr

## Floodlights

## HERCULED


IP66



HCL/ST (Symmetrical) AREA






HCL/P POWER




HCL/ST (Asymmetrical) AREA



Adjustable angle



To be able to meet the needs perfectly in field and field lighting in order to develop different optical structures by Litpa. In the standard field illumination, the optical structure of the Herculed / Area model is symmetrical and asymmetrical. On facades and more sensitive lighting Herculed Power meets all kinds of lighting needs.



Code	HCL/ST/S Symmetrical	HCL/ST/AS Asymmetrical	HCL/P
LED	High Efficiency Power Led	High Efficiency Power LED	High Efficiency Multi-Power
System Power	100 W 150 W 200 W 240 W	100 W 150 W 200 W 250 W	200 W 240 W
Light Flux	13.000 lm 19.500 lm 25.000 lm 30.000 lm	14.200 lm 20.600 lm 26.100 lm 30.700 lm	20.000 lm 25,500 lm
Color Temperature	3000 K 4000 K 5000 K	3000 K 4000 K 5000 K	3000 K 4000 K 5000 K
Voltage	220V - 50Hz		
Body	Aluminum injection		
Diffuser	Tempered glass		
Optic	Miro-Silver Aluminum	Miro-Silver Aluminum	Narrow-Wide Angle Reflector
Box Dimensions	44x48x19cm	44x48x19cm	44x48x19cm
Weight	12.100 gr	12.000 gr	12.000 gr




## Floodlights



## MDL


IP65




MDL4



MDL3




MDL2




MDL1

MDL projectors are the most suitable solution for various outdoor lighting projects thanks to their high efficiency and various power(W) options. There are types with high luminous flux and lens types at angles suitable for the area to be illuminated.

The luminaires are easily mounted with the foot mechanism. When it is brought to the desired angle, the spring and gear mechanism fully locks the armature. In this way, angle shifts are prevented over time.



Code	a
MDL4	590 mm
MDL3	500 mm
MDL2	410 mm
MDL1	240 mm



Code	MDL4	MDL3	MDL2	MDL1
LED	High Efficiency Power Led			
System Power	200W	150W	100W	50W
Light Flux	21.000 lm	16.000 lm	10.800 lm	5.500 lm
Color Temperature	3000 K 4000 K 5000 K			
Voltage	220V - 50Hz			
Body	Aluminum			
Cooler	Aluminum injection			
Diffuser	Clear polycarbonate			
Weight	9.700 gr	8.100 gr	6.500 gr	

## Rotational Floodlights

### RTL

IP65



RTL 24



RTL 18



RTL 12




RTL 9




Louvre 1




Louvre 2




DMX Controller



30°




30°




45°

RTL 9 - 12



RTL 18 - 24



Code	RTL 9	RTL 12	RTL 18	RTL 24	
LED	High Efficiency Power LED				
System Power	12 W	15 W	22 W	28 W	40 W
Light Flux	1,145lm-30°	1,420lm-30°	2,300lm-15°	3,300lm-15°	4,290lm-15°
Colour Temperature	3000-4000-5000K, R-G-B-Amber, RGB				
Voltage	220V - 50Hz				
Body	Aluminum injection painted with electrostatic paint				
Cooler	Cooling from the body surface				
Optic	Impact resistance tempered glass and high efficient lenses				
Frame	Aluminum injection				
Colour	Grey				
Accessory	Standard cable or IP68 connector				
Box Dimensions	25x19x17cm		28x23x17cm		
Weight	2.500 gr	2.600 gr	3.100 gr	3.200 gr	






## LITPA QUANTUM - Large



IP66



QTM-L

Adjustable  
Mounting Bracket

Litpa Quantum is a wallwasher type of fixture produced for use in facade lighting. They can be used as white, red, green, blue, yellow and RGB to get the desired effect on the surface. DMX systems allow the realization of different scenarios for the fixture from one single center. It is possible to direct the area to light properly by virtue of the lens types that can be used at different angles.

QTM30 QTM60 QTM90 QTM120 

Code	a
QTM 30	320 mm
QTM 60	620 mm
QTM 90	920 mm
QTM 120	1.220 mm

Code	QTM/L30		QTM/L60		QTM/L90		QTM/L120	
LED Type	High efficiency Power LED							
LED Quantity	Single	RGB	Single	RGB	Single	RGB	Single	RGB
	24pcs	24pcs	48pcs	48pcs	72pcs	72pcs	96pcs	96pcs
System Power	26W	30W	52W	40W	75W	60W	100W	80W
Light Flux	3.390lm	-	7.030lm	-	10.200lm	-	13.600lm	-
LED Life	50.000hrs							
Body	Aluminum extrusion							
Cooler	Cooling from the body surface							
Diffuser	Polycarbonate							
Optic	High efficiency lens							
Lens Angle	12° - 60° and Ellipsoidal							
Colour Temperature	3000K - 4000K - 5000K, red, blue, green, amber,RGB, RGBW, tunable white							
Accessory	Waterproof connector							
Weight	1.5kg		2.6kg		3.2kg		4.25kg	

Luminous flux measured at 4000K with 60° lens

## Wallwasher

## LITPA QUANTUM - Slim


IP66



QTM/S



Opal Diffuser

Adjustable  
Mounting Bracket



Slim Series Litpa Quantum luminaires on the facade with subtle and elegant structures it provides optimum adaptation to the architectural structure by preserving itself. Foot structure can be adjusted at the desired angle. In this way, they can be assembled. Luminaires to be used with DMX systems suitable. Facade with color transitions using single and multiple colors or the desired effects can be provided in the environment.

QTM/S30

QTM/S60

QTM/S90


QTM/S120



Code	a
QTM/S 30	320 mm
QTM/S 60	620 mm
QTM/S 90	920 mm
QTM/S 120	1.220 mm

Code	QTM/S30	QTM/S60	QTM/S90	QTM/S120	QTM/S120
LED Type	High efficiency Power LED				
LED Quantity	12pcs	24pcs	36pcs	48pcs	48pcs
System Power	14W	28W	40W	51W	102W
Light Flux	1800lm	3600lm	5400lm	7180lm	11250lm
LED Life	50.000hrs				
Body	Aluminum extrusion				
Cooler	Cooling from the body surface				
Diffuser	Polycarbonate				
Optic	High efficiency lens				
Lens Angle	12° - 60° and Ellipsoidal				20°
Colour Temperature	3000K - 4000K - 5000K, red, blue, green, amber				
Accessory	Waterproof connector				

Luminous flux measured at 4000K with 60° lens except 102W




## Wallwasher


# LITPA QUANTUM EVO

IP66



The integrated sealing lens structure on the body surface allows the luminaire to be successfully used in outdoor applications. It provides excellent comfort thanks to its special lens and light cutter structure in areas where light escape is not desired. However, it does not compromise light efficiency.




QTM/EVO



Adjustable  
Mounting Bracket



Code	a
QTM/EVO 50	505 mm
QTM/EVO 100	995 mm



Code	QTM/EVO 50	QTM/EVO 100
LED Type	High efficiency Power LED	
LED Quantity	12pcs	24pcs
System Power	27W	54W
Light Flux	2.700lm	5.400lm
Body	Aluminum extrusion	
Cooler	Cooling from the body surface	
Diffuser	Polycarbonate	
Optic	High efficiency lens	
Colour Temperature	3000K - 4000K - 5000K, red, blue, green, amber	
Accessory	Waterproof connector	



## Led Tube

### LDD

### IP66




Led Tube luminaires with high protection class (IP) ratings are the essential elements of outdoor lighting. They are often preferred because of the fact that they do not create an unwanted image on a continuous straight line on the façade. LDD luminaire is convenient for facade lighting and offers lighting effects for roof eaves hidden niches. Litpa LDD Led Tubes fulfill the functions of operating without any problems in a long lifetime, thanks to high lumen values and quality components used in production.


Mounting brackets are optional  
Adjustable mounting accessories provides angle based mounting option  
LDD fixture is convenient for double side light effect applications  
Wide range of length option from 50cm to 120cm  
Wide range of colour temperature option from 2700K to 6500K  
Colour Rendering index CRI > 80  
Offer best solution for linear applications and provides homogenous light effect  
Multiple fixture can be controlled by one ballast vary up to 240W power consumption at the linear effect applications  
Red-Green-Blue, RGB option is available



Ease of installation



IP67 Connector



Code	LDD
LED	High Efficiency Midpower LED
System Power	18W/m
Light Flux	1533 lm/m
Colour Temperature	3000 - 4000 - 5000 K, R,G,B -RGB
Voltage	220V - 50Hz
Body	Acrylic body and end caps
Colour	Clear or opal body, gray end caps
Weight	250gr

## Ground Recessed

## HADES

## IP67



HYL 9




HYL 12




HYL 18



HYL 24



DMX Controller



Ground recessed fixture series named HADES fixtures are designed for use in interior and exterior spaces and are extremely efficient fixtures for lighting of facades, walls, columns, and trees. High efficiency LEDs increase the life of the fixtures and eliminate the heating problems.

These fixtures are resistant to shock thanks to especially reinforced glass structures thereof. They can be produced in desired light color temperature and in different light colors. They are able to create the desired aesthetic effect in the area by being connected to the DMX control unit and by using as RGB.



HYL OP

HYL 9 - 12



HYL 18 - 24



Code	HYL 9	HYL 12	HYL 18	HYL 24
LED	High Efficiency Power LED			
System Power	12 W	15 W	22 W	28 W
Light Flux	1,050 lm	1,411 lm	2,300 lm	3,300 lm
Colour Temperature	3000-4000-5000-6500 K, R-G-B-Amber, RGB			
Voltage	220V - 50Hz			
Body	Aluminum injection			
Frame	Type 304 Stainless steel			
Cooler	Cooling from the body surface			
Lens Angle	10° - (14°+39°) - 30° - 45°			
Optic	Impact resistance tempered glass and high efficient lenses			
Accessory	Standard cable or IP68 connector			
Box Dimensions	26x26x25cm		32x32x27cm	
Weight	2.500gr	2.600gr	3.200gr	3.300gr




## Ground Recessed

# YLW


# IP67



These highly efficient linear fixtures can be used as ground recessed fixtures in interior and exterior lighting. They have a long lifetime thanks to their stainless steel frames, highly resistant heat-treated glasses and corrosion resistant aluminum bodies that can transfer heat easily. Different LEDs can create the color temperature of the light generated in the fixture. They can be used as RGB by connecting to the DMX control unit.




DMX Controller



Code	a	b	c	d	e	f	Cut-Out
YLW 40	402 mm	390 mm	107 mm	90 mm	80 mm	65 mm	82X395mm
YLW 70	562 mm	550 mm	107 mm	90 mm	80 mm	65 mm	82X555mm
YLW 100	1058 mm	1046 mm	107 mm	90 mm	80 mm	65 mm	82X1050mm

Code	YLW 40	YLW 70	YLW 100
LED	High Efficiency Power LED		
System Power	10 W	21 W	40 W
Light Flux	1.050 lm	2.200 lm	4.050 lm
Colour Temperature	3000-4000-5000-6500K, R-G-B-Amber, RGB		
Voltage	220V - 50Hz		
Body	Aluminum extrusion		
Cooler	Cooling from the aluminum body surface		
Lens Angle	12° - (14°+39°) - 25° - 46° - 61°		
Diffuser	Impact resistance tempered glass with 8mm thickness		
Optic	High efficient lenses		
Frame	Type 304 stainless steel		
Accessory	Standard cable or IP68 connector		
Box Dimensions	42x12x10 cm	58x12x10 cm	108x12x10 cm
Weight	2.230 gr	3.350 gr	6.250 gr



## Flowers / Grass Lighting

## MSH


## IP65



Special indirect lawn and garden lighting system designed with high efficiency LED technology within range of 3 to 9 W for outdoor applications. The system is preferred in architectural applications generally thanks to the indirect light beam coming from the module. Bright white paint with reflective properties has been used in the interior body paint with an eye to benefit maximum from the light coming from the LED modules.

MSH model Grass Fixtures can be employed for lighting lawn and garden plants and highlighting details in architectural garden lighting. Color options are available with a view to provide different light effects. Length of the fixture can be arranged according to the desired height.

Durability in all kinds of outdoor conditions thanks to corrosion-resistant injection molded aluminum outer body thereof. Has a long life by virtue of the injection molded aluminum with IP65 protection degree and does not require maintenance thanks to the LED module thereof. It can provide different applications with its free standing model and with the model which can be driven into the ground.



Code	MSH
LED	High Efficiency Power LED
System Power	4,5 W
Light Flux	75 lm
Colour Temperature	3000 - 4000 - 5000 K / R-G-B
Voltage	220V - 50Hz
Body	Aluminum injection LED moduls
Lens	Lenses with opal diffuser effect
Glass	3 mm thick and tempered glass
Colour	Grey



## Bollard - Globe

## BOLLARD

IP54 - IP66



IP54

8040



IP54

8050




IP66

LUXOR



IP54

3007



CB10 TOP VIEW


CB10

CB11



Our bollards are preferred in various areas of application such as lighting of walking trails, parks, recreational areas, residential areas, outside the stadiums and etc.


Highly efficient LED systems have been used in this product like in all of our LED products. System power is within the range of 12 W to 24 W and the product life has been extended by easy installation and maintenance.



Code	8040	8050	CB10	CB11	3007
LED	Mid-Power LED		Power LED		Mid-Power
System Power	15 ~ 22 W		12W	2x12W	15-22W
Light Flux	700 ~ 1000 lm		1300lm	2600lm	700~1000lm
Colour Temperature	3000 - 4000 - 5000 K - R-G-B				
Voltage	220V - 50Hz				
Body	Aluminum				
Diffuser	Opal or Prismatic		Polycarbonate		Opal
Box Dimensions	21x21x104 cm		21x21x104 cm		51x51x52 cm
Weight	5,200 gr		—		2,650 gr

## Garden Lighting


## LSH



## IP65

This is a special lighting system designed with high-efficiency LED technology within the range of 3 W to 9 W for outdoor applications. They can be used for architectural garden lighting, tree lighting and for underlining the details.

Corrosion-resistant cast aluminum outer body ensures durability against all outdoor conditions. Two different types of mounting options are offered. It is in two models as foot structure fixed to the ground and piled model which can be stuck into earth.



Code	LSH
LED	High Efficiency Power LED
System Power	8 W
Light Flux	720 lm
Color Temperature	3000 - 4000 - 5000 K, R-G-B - Amber
Voltage	220V - 50Hz
Bpdy	Aluminum extrusion painted with electrostatic paint
Cooler	Cooling from the body surface
Lens Angle	15° - 30° - 45°
Diffuser	4 mm thick and tempered glass
Color	Gray
Box Dimensions	22x21x43cm
Weight	1.100 gr

## D-LYD


IP65



Code	D-LYD
LED	High Efficiency Mid-Power and COB
System Power	5W
Colour Temperature	3000 - 4000 - 5000 - 6500 K, RGB
Voltage	220V - 50Hz
Body	Aluminum injection
Lens	Opal
Cooler	Cooling from the body surface
Colour	Grey
Box Dimensions	13x15x12 cm
Weight	450 gr

## D-LSD

IP65



Code	D-LSD
LED	High Efficiency Mid-Power Led
System Power	8 W
Colour Temperature	3000 - 4000 - 5000 - 6500 K
Voltage	220V - 50Hz
Body	Aluminum injection
Diffuser	Acrylic transparent lens
Cooler	Cooling from the body surface
Colour	Grey
Box Dimensions	13x15x18 cm
Weight	650 gr

## D-LFB9

IP65



Code	D-LFB9 / D-LFK9
LED	High Efficiency Power LED
System Power	12 W
Light Flux	1200 lm
Colour Temperature	3000 - 4000 - 5000 K, R-G-B
Voltage	220V - 50Hz
Body	Aluminum injection painted with electrostatic paint
Cooler	Cooling from the body surface
Lens Angle	12°, 25°, 29°, 61° Lens
Glass	3 mm thickness tempered
Colour	Grey




D-LFK9




## Canopy Luminaires

## PETROLED

IP65





PTL/S




PTL/AS


PETROLED Series fixtures produced as canopy fixtures and which can be used under fringes are robust fixtures and are resistant against exterior ambient conditions with durable die-cast aluminum body. The desired light distribution is ensured while maintaining high optical yield at the same time thanks to Miro-Silver reflectors made from material produced especially for LEDs by the German company named Alanod. Fixtures can be produced symmetrical or asymmetrical according to requirement.



PTL/S



PTL/AS




Code	PTL 40/S PTL 40/AS	PTL 60/S PTL 60/AS	PTL 80/S PTL 80/AS
LED	High Efficiency COB LED		
System Power	40 W	60 W	80 W
Light Flux	4.500lm	6.500 lm	8.500 lm
Colour Temperature	3000 - 4000 - 5000 K		
Voltage	220 Volt - 50 Hz		
Body	Aluminum injection		
Diffuser	Impact resistance tempered glass serigraphic printing		
Reflector	Alanod brand vacuum anodized Miro -Silver aluminum		
Cooler	Cooling from the body surface		
Colour	White		
Accessory	Recessed ceiling apparatus		
Box Dimensions	43x43x17 cm		
Weight	11.100 gr		



## Tunnel Lighting


### HCL-T

IP66



HCL/T

BASIC






HCL/T

STANDARD

Litpa Tunnel Luminaires have produced high quality optic with high technology. It presents excellent technical lighting conditions of tunnel luminaires. Dust and water-resistant body structure and extremely high corrosion resistance.

It provides a long life with. Thanks to the aluminium body structure provides well-ordered cooling.



	BASIC		STANDARD			
Code	HCL/T80	HCL/T150	HCL/T100	HCL/T150	HCL/T200	HCL/T240
LED	High Power LED					
Sytem Power	80 W	150 W	100 W	150 W	200 W	240 W
Light Flux	8.900lm	13.900lm	14.200lm	20.600lm	26.100lm	30.700lm
Color Temperature	3000-4000-5000K					
Voltage	220V - 50Hz					
Body	Aluminum injection					
Glass	Impact resistance tempered glass					
Optic	High efficiency lens					
Weight	13.000 gr					







# INDOOR LIGHTING

## LUMINAIRES



## Downlight


## SHOPLED

IP20

High energy-efficient SHOPLED downlight fixtures can be used in many areas with the large usage area thereof including shops, hotels, restaurants, cafés, educational areas hospital and houses. They can meet the investment in the usage area after a very short time even with the change of the existing systems. The lives of used COB LEDs are very long due to their fixture bodies and the aluminum coolers placed thereon.



SLG 104



SLG 160


SLG 165




SLG 195

SLG 200


SLG 104




SLG 160 - SLG 165



SLG 195 - SLG 200



Code	Cut-Out
SLG 104	120 mm
SLG 160	172 mm
SLG 165	172 mm
SLG 195	205 mm
SLG 200	205 mm



Code	SLG 104	SLG 165 SLG 160	SLG 195 SLG 200
LED	High Efficiency COB LED		
LED Power	13 W	27 W	36 W
Light Flux	1,280 lm	2,560 lm 2,300 lm	3,300 lm 3,000 lm
Colour Temperature	3000 - 4000 - 5000 K		
Voltage	220V - 50Hz		
Body	Die-cast aluminum frame painted with 80 micron thick		
Reflector	99% pure aluminum		
Diffuser	Acrylic diffuser or tempered glass		
Cooler	Aluminum extrusion		
Colour	White		
Box Dimensions	30x44x21 cm(6pcs)	47x47x18 cm(4pcs) 21x23x18 cm(1pcs)	25x26x24 cm(1pcs) 26x26x25 cm(1pcs)
Weight	4.400 gr(6pcs)	5.250gr(4pcs) 1.350gr(1pcs)	1.800 gr(1pcs) 1.650 gr(1pcs)



## Downlight

## PUNTO

IP20  
IP40 Optional

High permeability opal diffuser transfers light to the environment in soft a way. High lighting efficiency and a clear appearance is achieved thanks to special reflectors used in the inner side surface of the fixture. Affordability, efficiency and slimness are three words that summarize Punto Series downlights best.



SSL 104




SSL 160

SSL 200




SSL 235



Code	Cut-Out
SSL 104	120 mm
SSL 160	172 mm
SSL 200	205 mm
SSL 235	245 mm

Code	SSL 104	SSL 160	SSL 200	SSL 235
LED	High Efficiency Mid-Power LED			
LED Power	13 W	20 W	22 W	32 W
Light Flux	1.120 lm	1.500 lm	1.900 lm	2.300 lm
Colour Temperature	3000 - 4000 - 5000 K			
Voltage	220V - 50Hz			
Body	Aluminum injection frame.			
Diffuser	Opal			
Cooler	Cooling from the body surface			
Colour	White			
Box Dimensions	15x15x7cm	22x22x7cm	25x25x7cm	30x30x7cm
Weight	250 gr	450 gr	450 gr	550 gr



## Downlight

## MSG

IP20

High energy-efficient SHOPLED downlight fixtures can be used in many areas with the large usage area thereof including shops, hotels, restaurants, cafés, educational areas hospital and houses. They can meet the investment in the usage area after a very short time even with the change of the existing systems.




MSG 160/C





MSG 160/D



MSG 200/C




MSG 200/D



MSG 160/C - MSG 160/D



Ø 202mm




Ø 202mm

MSG 200/C - MSG 200/D



Ø 235mm



Ø 235mm

Code	Cut-Out
MSG 160/C	178 mm
MSG 160/D	178 mm
MSG 200/C	206 mm
MSG 200/D	206 mm

Code	MSG 160/C	MSG 200/C	MSG 160/D	MSG 200/D
LED	COB LED			
System Power	14W 20W 27W	14W 20W 27W 40W	14W 20W	14W 20W
Light Flux	1.750lm 2.450lm 3.200lm	1.750lm 2.450lm 3.200lm 4.250lm	1.250lm 1.700lm	1.250lm 1.700lm
Colour Temperature	3000 - 4000 - 5000 K			
Voltage	220V - 50Hz			
Body	Aluminum injection frame painted with 80 micron thick			
Lens	High efficiency lens (MSG160/D - MSG200/D)			
Cooler	Aluminum injection			
Colour	White			
Weight	850gr	1.000gr	850gr	1.000gr

## Downlight

## MSG


## IP20 - IP54



MSG 160/O





MSG 160/WP IP54



MSG 200/O




MSG 200/WP IP54




High energy-efficient SHOPLED downlight fixtures can be used in many areas with the large usage area thereof including shops, hotels, restaurants, cafés, educational areas hospital and houses. They can meet the investment in the usage area after a very short time even with the change of the existing systems.

## MSG 160/O - MSG 160/WP



## MSG 200/O - MSG 200/WP



Code	Cut-Out
MSG 160/O	178 mm
MSG 160/WP	178 mm
MSG 200/O	206 mm
MSG 200/WP	206 mm

Code	MSG 160/O	MSG 200/O	MSG 160/WP	MSG 200/WP
LED	Mid-Power LED			
System Power	14W 20W 27W	14W 20W 27W	14W 20W 27W	14W 20W 27W
Light Flux	1.110lm 1.500lm 2.000lm	1.200lm 1.700lm 2.200lm	1.110lm 1.500lm 2.000lm	1.200lm 1.700lm 2.200lm
Colour Temperature	3000 - 4000 - 5000 K			
Voltage	220V - 50Hz			
Body	Aluminum injection frame painted with 80 micron thick			
Diffuser	Opal diffuser			
Cooler	Aluminum injection			
Colour	White			
Weight	850gr	1.000gr	850gr	1.000gr



## Downlight

## FASHIONLED

IP20



RLK 13





RLK 27



RLP 13

RLP 27

FASHIONLED is type of fixture which can be easily used in a practical manner thanks to the design thereof allowing it to be moved and turned to all directions easily by mounting on rails in case of need for store, shop window and emphasized lighting. Multiple blades placed thereon transfers the cooling area from an extremely large surface to environment. Thus, highly efficient COB LEDs can have a very long life. Reflector options with 10 °, 30 ° and 60 ° are available. A wide choice is offered to users with different strengths and body structures.



Code	RLK 13	RLP 13	RLK 27	RLP 27
LED	High Efficiency COB LED			
LED Power	13 W		27 W	
Light Flux	1,350 lm		2.500 lm	
Colour Temperature	3000 - 4000 - 5000 K			
Voltage	220V - 50Hz			
Body	Aluminum extrusion and aluminum frame			
Reflector	99% pure aluminum			
Diffuser	3 mm thickness transparent tempered glass			
Cooler	Aluminum extrusion			
Colour	White			
Box Dimensions	22x17x29 cm		25x25x40 cm	
Weight	900 gr		2.700 gr	



## Downlight


## FASHIONLED

IP20

RLK / M series luminaires which are including lens produced with aluminum body provide the desired optical requirements for the spaces, while they attract attention as highly efficient rail spots. Luminaires are compact body, easily orientable and mountable luminaire. Luminaires are manufactured with quality material and simple design concept.



RLK/M



Code	RLK/M
LED	High Efficiency LED
System Power	32 W
Light Flux	3.350 lm
Colour Temperature	3000 - 4000 - 5000 K
Voltage	220V - 50Hz
Body	Aluminum extrusion and aluminum frame
Reflector	99% Pure aluminum
Optic	Ledil Lens
Colour	White



DML 1



DML 2



DML 3



DML 4

## Downlight


## SHOWLED

IP20



SHOWLED is a highly efficient and economical type fixture with a wide range of applications used in interior. Spots in 2, 3 and 4-piece units are designed to move independently from each other. In this way, light from a single fixture can be transmitted simultaneously to different directions.

Mounting feet press firmly on the surface to prevent the gap between ceiling and the mounting frame and bad appearance due to assembly can be prevented. Different reflector structures offer possibilities to meet your requirements from the optical point of view. High LED efficiency and highly efficient reflectors thereof will provide significant energy savings for your business.




220mm



410mm



600mm




220mm




410mm

Code	Cut-Out
DML-1	180x180 mm
DML-2	380x180 mm
DML-3	570x180 mm
DML-4	380x380 mm

Narrow Angle



Wide Angle



Code	DML 1	DML 2	DML 3	DML 4
LED	High Efficiency COB LED			
LED Power	1x13 W 1x27 W 1x36 W	2x13 W 2x27 W 2x36 W	3x13 W 3x27 W 3x36 W	4x13 W 4x27 W 4x36 W
Light Flux	1,350 lm 2,650 lm 3,350 lm	2,700 lm 5,300 lm 6,700 lm	4,050 lm 7,950 lm 10,050 lm	5,400 lm 10,600 lm 13,400 lm
Colour Temperature	3000 - 4000 - 5000 K			
Voltage	220V - 50Hz			
Body	Made of 1 mm thick sheet steel and painted with powder paint			
Reflector	1 mm thick anodized aluminum vacuum 99.9 %			
Cooler	6063 T5 aluminum extrusion			
Colour	Grey			
Box Dimensions	24x24x21 cm	24x45x21 cm	24x64x21 cm	45x45x21 cm
Weight	2.100 gr	4.100 gr	6.200 gr	8.200 gr


## Downlight

## GALAXYLED

IP20




DL 2003



DL 2004


DL 2005



DL 2006


GALAXYLED fixtures are suitable for use in many areas such as particularly hotels, restaurants, plazas, shopping malls and stores. COB LEDs furnish extremely good fixture efficiency and stable operation by virtue of high-efficient reflectors and coolers manufactured from aluminum material with high-grade heat transfer. They lower the amount of visual pollution to minimum levels and help you to achieve the desired lighting levels. They are suitable for effects and decorative lighting with different optical and power options.

DL 2003-2004-2005-2006




Code	Cut-Out
DL-2003	Ø 93 mm
DL-2004	Ø 93 mm
DL-2005	Ø 93 mm
DL-2006	Ø 93 mm


DL 2003-C1




DL 2003-C2




DL 2004



DL 2005



DL 2006



Code	DL 2003 C1 DL 2003 C2	DL 2004	DL 2005	DL 2006	
LED	High Efficiency COB LED				
System Power	8 W	8 W	8 W	8 W	
Light Flux	640 lm 620 lm	620 lm	670 lm	730 lm	
Colour Temperature	3000 - 4000 - 5000 K				
Cooler	Aluminum extrusion				
Voltage	220V - 50Hz				
Body	Aluminum injection frame				
Reflector	High pure aluminum				
Diffuser	65 mm diameter 3 mm thick transparent tempered glass				
Colour	White				
Box Dimensions	15x15x12.5 cm			15x15x13cm	
Weight	490 gr	500 gr	550 gr	480 gr	600 gr


## Downlight

## SFR

## IP20



SFR 13/S White



Chrome

Gold



SFR 13/S




SFR 13/L

SFR model downlight fixtures are indispensable application elements for interior lighting with their compact and simple structure. They can be applied in hotels, schools, shopping centers and many other places. Reflectors used in the fixture to perform this task without requiring extra frame and provide an appearance integrated with the ceiling and which does not harm the aesthetics structure of the area thanks to the fine structure thereof. They offer a perfect solution in locations where dark light is desired and glare is unwanted by using black reflector.


SFR 13/S

SFR 13/L



SFR 13/S White

SFR 13/S Black



Code	Cut-Out
SFR 13/S	110 mm
SFR 13/L	105 mm

Code	SFR 13/S	SFR 13/L
LED	High Efficiency COB LED	
LED Power	13 W	
Light Flux	833lm - White Reflector 708lm - Black Reflector	833lm-White Reflector
Colour Temperature	3000 - 4000 - 5000 K	
Voltage	220V - 50Hz	
Body	Manufactured from spinning aluminum and painted with 80 mm electrostatic powder paint	
Reflector	Spining aluminum	
Cooler	Aluminum extrusion	
Colour (Reflector)	White or Black	
Box Dimensions	14x13x13cm	16x13x13cm
Weight	450 gr	450 gr





## Downlight

### SMG-L


IP20



The SMG-L luminaires are perfectly matched to the ceiling with special pulley structure and show a nice posture in the ceilings with aesthetic durability in the applied areas. The orientation of the luminaire provides flexibility in positioning the ceiling. With the high efficiency LED types and power options used, desired lighting levels can be provided easily.




Ø 201 mm




Ø 201 mm

147 mm

Narrow Angle



Wide Angle



Code	SMG-L	
LED	High Efficiency COB LED	
LED Power	13 W	27 W
Light Flux	1.280 lm	2.500 lm
Colour Temperature	3000 - 4000 - 5000 K	
Voltage	220V - 50Hz	
Body	Aluminum injection frame painted with 80 micron electrostatic powder paint	
Cooler	Aluminum extrusion	
Glass	3mm thick tempered glass	
Colour	White	
Box Dimensions	21x23x19 cm	
Weight	1.470 gr	



## Downlight Systems

### DR (Frames)

IP20



DR1



DR2

Adjustable



DR3

IP54



DR4



DR5



DR6


Adjustable



DR7

The LITPA Downlight systems ensure that different models and luminaire fittings can be used with different power options. Each type of pulley, the LED light source with 3 different wattage can be easily installed with the integrated cooler.

There are options to use reflectors and lenses in luminaires. Thanks to the usage of optics, the light omitting from the luminaire is only and only directing to the enlightening areas. By this way energy conservation can be applied.



### Darklight apparatus



Darklight apparatus narrows the angle of light coming out of the luminaire (available with DR1 - DR3- DR4 - DR5 - DR7)

Code	DR1	DR2	DR3	DR4	DR5	DR6	DR7
LED	High efficiency COB LED						
System Power	4W 10W 15W	4W 10W 15W	4W 10W 15W	4W 10W 15W	4W 10W 15W	4W 10W 15W	4W 10W 15W
Light Flux	400lm 780lm 1170lm	350lm 650lm 980lm	360lm 690lm 1050lm	400lm 800lm 1200lm	380lm 750lm 1130lm	300lm 580lm 900lm	410lm 800lm 1200lm
Colour Temperature	3000 - 4000 - 5000 K						
Voltage	220V - 50Hz						
Body	Aluminum injection frame						
Optic	%99 pure aluminum or high efficiency lens						
Cooler	Aluminum injection						
Colour	White						

## Downlight Systems

### DOT (Power Options)

IP20

This lighting system alone needs different visual, optical and light can be afforded. Some pulley types can be directed in vertical luminaire that permits. Anti-glare accessories can be applied to all pulley types.



DOT1



DOT2



DOT3


#### Optic



Lens



Reflector



		LUMINAIRE HEIGHT (h)		
		POWER		
Frame	DR1	74mm	84mm	92mm
	DR2	87mm	97mm	105mm
	DR3	65mm	75mm	83mm
	DR4	82mm	92mm	100mm
	DR5	94mm	104mm	112mm
	DR6	87mm	97mm	105mm
	DR7	90mm	100mm	105mm




#### CUT-OUT

Frame	Cut-Out
DR1	88mm
DR2	90mm
DR3	70mm
DR4	80x80mm
DR5	90mm
DR6	75mm
DR7	90mm




## ELD 75



Rotatable



Ø 90mm




Ø 90mm

Ø 80mm

IP20

Code	ELD 75/5	ELD 75/8
LED	High Efficiency Power LED	
System Power	5 W	9 W
Light Flux	450 lm	850 lm
Colour Temperature	3000 - 4000 - 5000 K	
Voltage	220V - 50Hz	
Body	Aluminum injection	
Cooler	Aluminum	
Reflector	Aluminum	
Glass	3mm thick transparent tempered	
Box Dimensions	12x12x12 cm	
Weight	290 gr	
Cut-Out	Ø 75 mm	

## ELD 125



Rotatable



Ø 138mm



Ø 138mm



Ø 110mm

IP20


Code	ELD 125
LED	High Efficiency COB LED
System Power	16 W
Light Flux	1.060 lm
Colour Temperature	3000 - 4000 - 5000 K
Voltage	220V - 50Hz
Body	Aluminum injection
Cooler	Aluminum
Reflector	Aluminum
Glass	3mm thick transparent tempered
Box Dimensions	15x15x15 cm
Weight	740 gr
Cut-Out	Ø 125 mm

# L1671

IP20 - IP54




Code	L1671/5	L1671/8
LED	COB Led	Multichip Led
System Power	5 W	9 W
Light Flux	480 lm	660 lm
Colour Temperature	3000 - 4000 - 5000 K	
Voltage	220V - 50Hz	
Body	Aluminum injection	
Reflector	99% pure aluminum	
Cooler	Aluminum extrusion	
Glass	3mm thick, transparent, tempered	
Box Dimensions	30x44x15 mm (6pcs)	
Weight	2.300 gr (6pcs)	
Cut-Out	Ø 68 mm	




# HRN1

IP20




Code	HRN113	HRN127	HRN213	HRN227
LED	High Efficiency COB LED			
LED Power	13 W	27 W	2x13 W	2x27 W
Light Flux	1.230 lm	2.350 lm	2.460 lm	4.700 lm
Colour Temperature	3000 - 4000 - 5000 K			
Voltage	220V - 50Hz			
Body	0,6 mm thick DKP			
Reflector	99.9 % purity aluminum			
Cooler	6063 T5 aluminum extrusions			
Colour	White, Black			

# HRN2




Code	h	a	b
HRN113	125mm	120mm	120mm
HRN127	140mm	120mm	120mm
HRN213	125mm	230mm	120mm
HRN227	140mm	230mm	120mm

## LKG1




## LKG2






IP20

Code	LKG 1		LKG 2	
LED	High Efficiency LED			
System Power	5 W	8 W	2x5 W	2x8 W
Light Flux	480lm	660 lm	960 lm	1320 lm
Colour Temperature	3000 - 4000 - 5000 K			
Voltage	220V - 50Hz			
Body	1 mm thick DKP sheet painted with electro-static powder paint			
Reflector	High efficiency aluminum			
Cooler	Aluminum extrusion			
Frame	1,5mm thick DKP, inner frame aluminum injection			
Box Dimension	30x44x15 cm (6pcs)			
Weight	3.200 gr (6pcs)		5.500 gr (6pcs)	
Cut-Out	93X93 mm		93X181 mm	

LKG1




LKG2






## PGH




Code	PGH
LED	High Efficiency Mid-Power LED
System Power	10 W - 15 W - 20 W
Light Flux	840 lm - 1.170 lm - 1.230 lm
Colour Temperature	3000 - 4000 - 5000 K
Voltage	220V - 50Hz
Body	0.6mm made DKP steel sheet and painted with 80 micron thickness.
Diffuser	High permeable opal
Cooler	Cooling from the body surface
Colour	Grey
Box Dimensions	220x220x175 mm

IP20




## PGH/M



Code	PGH/MR	PGH/MOP
LED	High efficiency LED	
System Power	5W	5W
Colour Temperature	3000 - 4000 - 5000 K	
Voltage	220V - 50Hz	
Body	0.6mm DKP sheet. Painted with electro-static powder paint.	
Reflector	Aluminum	—
Diffuser	—	Opal
Colour	Grey	

IP20





## Surface Mounted


### SCP/S

IP54




These round-shaped products are surface mounted fixtures. Since light can be extremely homogenous and the protection class is high, the usage of areas are also quite large. Luminaires can be made at two different heights. Luminaires can be more functional by offering kit and sensor mounting option.

### SCP/N




Code	SCP/S	SCP/N
LED	High Efficiency Mid-Power LED	
Power	24W	
Light Flux	2.050 lm	
Driver	Included	
Colour Temperature	3.000 - 4.000 - 5.000 K	
Voltage	180 -240 V / 50hz	
Body	Polycarbonate	
Diffuser	Polycarbonate - opal	
Emergency Kit	—	1 - 3 hrs

## PNS




Code	PNS
LED	High Efficiency Mid-Power LED
System Power	13 W
Light Flux	800 lm
Colour Temperature	3000 - 4000 - 5000 K
Voltage	220V - 50Hz
Body	Spinning sheet
Frame	1,5mm thick DKP
Diffuser	1,2mm Opal
Colour	White, grey, black
Optional	1 hrs kit

IP20



## RLP/S




Code	RLP/S 13	RLP/S 27
LED	High Efficiency COB LED	
LED Power	13 W	27 W
Light Flux	1,350 lm	2.500 lm
Colour Temperature	3000 - 4000 - 5000 K	
Voltage	220V - 50Hz	
Body	Aluminum extrusion and aluminum frame	
Reflector	99% pure aluminum	
Diffuser	3 mm thickness transparent tempered glass	
Cooler	Aluminum extrusion	
Colour	White	

IP20

RLP/S 13



RLP/S 27




## SLK



Code	SLK/18	SLY/15	SLY/18	SLY/M18 Light Sensor Type
LED	High Efficiency Mid-Power Led			
Power	18W	15W	18W	18W
Luminous Flux	1800lm	1380lm	1550lm	1550lm
Colour Temperature	3.000 K	4.000 K	4.000 K	4.000 K
Voltage	180 -240 V / 50hz			
Body	Polycarbonate body			
Diffuser	Polycarbonate opal			
Weight	900 gr	400 gr	615 gr	615 gr

IP44

## SLY



SLK



SLY

Code	a
SLY/15	220 mm
SLY/18	280 mm



## Office Lighting

## OFISLED

IP20




LGS 60-60/3




LGS 60-60/4

LGS has been developed to transfer high LED technology to office lighting. Production is possible for all types of suspended ceilings. Therefore, production is made according to the brand/model of the suspended ceiling to be used. Glare and screen reflections have been taken into consideration in the optical design of the fixture which are the most important requirements in offices and Cat-1 Cat-2 types of the fixture have been developed. OFISLED is a lighting system which meets its investments by the savings it provides by renewal of existing systems thanks to high effectiveness of the LEDs and fixture efficiency compared to conventional fluorescents and T5 fixtures.



	Code	a	b	Cut-Out
GYPSUM	LGS 001 30-60	295mm	595mm	280x580mm
	LGS 001 60-60	595mm	595mm	580x580mm
	LGS 001 30-120	295mm	1195mm	280x1180mm
CLIP-IN	LGS 002 30-60	299mm	599mm	-
	LGS 002 60-60	599mm	599mm	-
	LGS 002 30-120	299mm	1199mm	-
MODULAR	LGS 300 30-60	295mm	595mm	-
	LGS 300 60-60	595mm	595mm	-
	LGS 300 30-120	295mm	1195mm	-



Code	LGS 60-60/3	LGS 60-60/4	LGS 30-120/2
LED	High Efficiency Mid-Power LED		
System Power	27 W	35 W	52 W
Light Flux	3.000 lm	3.900 lm	5.200 lm
Colour Temperature	3000 - 4000 - 5000 K		
Driver	Osram or Tridonic		
Voltage	220V - 50Hz		
Body	0,6 mm A1 quality DKP sheet steel 80 micron powder paint		
Optic	Cat-1, Cat-2	Cat-1, Cat-2	Cat-1, Cat-2
Reflector (inner)	Alanod Miro-Silver 27 AG aluminum		
Reflector (outer)	(Cat1) Alanod Miro Silver27/4270 AG aluminum (Cat2) Alanod Miro-Silver 20/2000 AG aluminum		
Diffuser	2,8 mm microprismatic lens		
Cooler	Cooling from the body surface		
Colour	White		
Box Dimensions	67x61x9cm		30x122x9cm
Weight	5.000 gr		5.500 gr

## Office Lighting

## OFISLED

IP20  
IP40 Optional

This is a fixture model with a wide usage and application. The light coming from multiple LED sources in LGO fixtures passes through the opal diffuser and provides an extremely soft and homogeneous distribution to the environment. Production for all types of suspended ceilings is possible. Therefore, production is made according to the brand/model of the suspended ceiling to be used. This fixture, like all Litpa fixtures is highly efficient and economical.




LGO




LGO-MP (Micro-Prismatic diffuser)


Micro-prismatic diffuser creates variable effects according to your point of view



	Code	a	b	Cut-Out
GYPSUM	LGO 001 30-60	295mm	595mm	280x580mm
	LGO 001 60-60	595mm	595mm	580x580mm
	LGO 001 30-120	295mm	1195mm	280x1180mm
CLIP-IN	LGO 002 30-60	299mm	599mm	-
	LGO 002 60-60	599mm	599mm	-
	LGO 002 30-120	299mm	1199mm	-
MODULAR	LGO 300 30-60	295mm	595mm	-
	LGO 300 60-60	595mm	595mm	-
	LGO 300 30-120	295mm	1195mm	-
	LGO 300 60-120	595mm	1195mm	-




Code	LGO 60/20	LGO 60/30	LGO 60/40	LGO 60/45
LED	High Efficiency Mid-Power LED			
System Power	20 W	30 W	40 W	45 W
Light Flux	2.100 lm	3,300 lm	4,350 lm	4.600 lm
Colour Temperature	3000 - 4000 - 5000 K			
Voltage	220V - 50Hz			
Body	0,5mm thick DKP sheet steel. Frame made of 0,5mm thick DKP steel. 80 micron thick electrostatic powder paint			
Diffuser	Opal			
Cooler	Cooling from the body surface			
Colour	White			
Box Dimensions	65x64x14 cm			
Weight	4.500 gr			




## Office Lighting

## DARKZONE


IP20



LGR60/3




LGR60/2




LGR60/1

Glare is one of the most important lighting criteria in the illumination of places such as offices and laboratories.

Glare can be expressed at technical level by drawing and calculating the mathematical values. To make it easier to understand DarkZone and a similar luminaire are placed next to reduce luminaire efficiency. DarkZone series luminaires are extremely difficult to compete due to the luminaire efficiency up to 105lm/W



Code	Ceiling Type	a	b
LGR 60	Gypsum	595mm	595mm
LGR 60	Clip-In	599mm	599mm
LGR 60	Modular	595mm	595mm




Code	LGR60/3	LGR60/2	LGR60/1
LED	High Efficiency Mid-Power LED		
System Power	60 W	45 W	35 W
Light Flux	5.850 lm	4.250 lm	3.150 lm
Colour Temperature	3000 - 4000 - 5000 K		
Voltage	220V - 50Hz		
Body	0,6 mm A1 quality DKP sheet steel 80 micron powder paint		
Optic	Cat-1,Cat-2	Cat-1,Cat-2	Cat-1,Cat-2
Reflector	Polycarbonate		
Cooler	Cooling from the body surface		
Colour	White		
Box Dimensions	67x61x8cm		
Weight	3.7kg	2.8kg	1.9kg



## Office Lighting


## DARKZONE

IP20




PGR60/1

DarkZone series luminaire can be used with different designed luminaire structures thanks to the modules used. The inward curved PGR model offers a different aesthetic structure in spaces. The optical system with black reflector used in the luminaire reflect the black and white contrast to the places in style. It can be produced in accordance with different types of suspend ceilings. High efficiency LEDs and low-loss drivers are used to produce high efficiency luminaire efficiency



Code	Ceiling Type	a	b
PGR 60	Gypsum	595mm	595mm
PGR 60	Clip-In	599mm	599mm
PGR 60	Modular	595mm	595mm




Code	PGR60/1
LED	High efficiency Mid-Power LED
System Power	35W
Light Flux	3.150lm
Colour Temperature	3000 - 4000 - 5000 K
Voltage	220V - 50Hz
Body	0,6 mm A1 quality DKP sheet steel 80 micron powder paint
Optic	Cat-1,Cat-2
Reflector	Polycarbonate
Cooler	Cooling from the body surface
Colour	White
Weight	2.75kg

## Office Lighting

## LEG-PR / LEG-OP

IP20




LEG-PR




LEG-OP


Glare and screen reflections have been taken into consideration in the optical design of the LEG series fixtures which are direct-indirect fixtures which are the most important requirements in offices. The fixture has been developed in direct - indirect mixed optical structure according to Cat-1 and Cat-2 types. The fixture is produced in different optical structures as double parabolic and opal. It is designed to be used in a suitable way in any office perfectly.




	Code	a	b	Cut-Out
GYPSUM	LEG-PR 001	595mm	595mm	580x580mm
	LEG-OP 001	595mm	595mm	580x580mm
CLIP-IN	LEG-PR 002	599mm	599mm	-
	LEG-OP 002	599mm	599mm	-
MODULAR	LEG-PR 300	595mm	595mm	-
	LEG-OP 300	595mm	595mm	-



LEG-PR



LEG-OP





Code	LEG-PR	LEG-OP
LED	High Efficiency Mid-Power LED	
System Power	25 - 35 W	26 - 38 W
Light Flux	1700 - 2280lm	1490 - 2120 lm
Colour Temperature	3000 - 4000 - 5000 K	
Voltage	220V - 50Hz	
Body	0,6mm thick DKP sheet steel	
Reflector	0,4 mm thick DKP sheet	
Cooler	Cooling from the body surface	
Colour	White	
Box Dimensions	61x67x12 cm	61x67x12 cm
Weight	4.900 gr	5.100 gr

## Office Lighting


## MOON

IP20




Desired patterns can be created upon request

OLG Series fixtures offer your esteemed side an option with rounded and stylish forms with high efficiency. They can be used single while they provide a distinctive ambiance to the spaces they are used when using side by side and in multi usage.



	Code	a	b	Cut-out
<b>GYPSUM</b>	OLG 60 001	595mm	595mm	580x580mm
<b>CLIP-IN</b>	OLG 60 002	599mm	599mm	-
<b>MODULAR</b>	OLG 60 300	595mm	595mm	-



Code	OLG 60/27	OLG 60/35
LED	High Efficiency Mid-Power LED	
System Power	27 W	35 W
Light Flux	2,300 lm	3,050 lm
Colour Temperature	3000 - 4000 - 5000 K	
Voltage	220V - 50Hz	
Body	0,5 mm thick A1 quality DKP sheet steel. 80 micron electrostatic powder paint.	
Cooler	Cooling from the body surface	
Diffuser	1,2mm thick opal	
Colour	White	
Box Dimensions	62x62x10 cm	
Weight	5.200 gr	




## Office Lighting

## FNSB-K

IP20



FNSB-K series designed in the form of square to be driven into the ceiling allows soft lighting applications and the LED technology used ensures energy-saving substantially. Ensures practical solutions thanks to its compliance with different types of suspended ceilings as well as different power ranges.



Code	a	b	c	d	Cut-Out
FNSB-K 20	200 mm	200 mm	169 mm	82 mm	175X175 mm
FNSB-K 40	400 mm	400 mm	369 mm	82 mm	375X375 mm


Code	FNSB-K 20	FNSB-K 40
LED	High Efficiency Mid-Power LED	
System Power	10W - 20W	20W - 30W
Light Flux	960 lm - 1,790 lm	1,990 lm - 2,680 lm
Colour Temperature	3000 - 4000 - 5000 K	
Voltage	220V - 50Hz	
Body	0.6 mm thick DKP sheet steel	
Diffuser	1,2mm opal	
Cooler	Cooling from the body surface	
Frame	1.5 mm thick DKP sheet steel	
Colour	White	
Box Dimensions	22x22x10 cm	42x42x10 cm
Weight	2.000 gr	3.000 gr

## Office Lighting


## FNSB-Y

IP20  
IP40 Optional

FNSB-Y series designed in the form of circle to be driven into the ceiling allows soft and diffuse lighting applications and the LED technology used ensures energy-saving substantially. Ensures practical solutions thanks to its compliance with different types of suspended ceilings as well as different power ranges.



Code	a	b	Cut-Out
FNSB-Y 25	250 mm	82 mm	Ø 237 mm
FNSB-Y 35	350 mm	82 mm	Ø 327 mm
FNSB-Y 55	550 mm	82 mm	Ø 527 mm



Code	FNSB-Y 25	FNSB-Y 35	FNSB-Y 55
LED	High Efficiency Mid-Power LED		
System Power	17 W - 24 W	22 W - 30 W	42 W
Light Flux	1,800 lm - 2,530 lm	1,650 lm - 3,160 lm	3,510 lm
Colour Temperature	3000 - 4000 - 5000 K		
Voltage	220V - 50Hz		
Body	0.8 mm thick DKP sheet steel		
Diffuser	1,2mm opal		
Cooler	Cooling from the body surface		
Frame	1.5 mm thick DKP sheet steel		
Colour	White		
Box Dimensions	27x27x10 cm	37x37x10 cm	57x57x10 cm
Weight	1.950 gr	3.100 gr	6.550 gr

## Office Lighting

## LSS


IP20




LSS 60-60/4



LSS 60-60/3


LSS 30-120/2  
Double parabolic reflector  
(optional)

LSS luminaires, which are a surface mounted model of luminaire, are presented as a complete solution in the places such as offices and etc. in order to remove the problems of glare. It increases the productivity to the top level for the employees by increasing light quality in the work environment. They are produced with 2, 3 and four-lamelle according to the amount of the light requested. Thanks to high quality materials used, extremely high performance and savings are provided.



Code	a	b
LSS 60-60/4	600mm	600mm
LSS 60-60/3	600mm	600mm
LSS 30-30/2	300mm	300mm
LSS 30-120/2	300mm	1200mm

Code	LSS 60-60/4	LSS 60-60/3	LSS 30-30/2	LSS 30-120/2
LED	High Efficiency Mid-Power LED			
System Power	35 W	27 W	18 W	27 W
Light Flux	3,900 lm	3.000 lm	2,350 lm	3.000 lm
Colour Temperature	3000 - 4000 - 5000 K			
Driver	Osram or Tridonic			
Voltage	220V - 50Hz			
Body	0,6 mm A1 quality DKP sheet steel 80 micron powder paint			
Optic	Cat-1,Cat-2	Cat-1,Cat-2	Cat-1,Cat-2	Cat-1,Cat-2
Reflector (inner)	Alanod Miro-Silver 27 AG aluminum			
Reflector (outer)	(Cat1) Alanod Miro Silver27/4270 AG aluminum (Cat2) Alanod Miro-Silver 20/2000 AG aluminum			
Diffuser	2,8 mm microprismatic lens			
Cooler	Cooling from the body surface			
Colour	White			
Box Dimensions	67x61x9cm	67x61x9cm	37x31x9cm	127x31x9cm
Weight	5.700 gr	5.500 gr	2.800 gr	5.800 gr





## Office Lighting

## LSO




LSO 60-60




LSO 30-120

IP20  
IP40 Optional

LSO luminaires, which have a lot of usage areas, are used in the places where there are no opportunities of recessed ceiling by installing onto the surface. They are produced with the shape square and rectangle according to the needs and meets different needs of power. They are produced with the understanding of eye-pleasing simple, stylish structure and high quality production.



Code	a	b	h
LSO 30-30	370 mm	370 mm	80 mm
LSO 30-60	575 mm	300 mm	70 mm
LSO 60-60	605 mm	605 mm	70 mm
LSO 30-120	1150 mm	300 mm	70 mm




Code	LSO 30-30	LSO 30-120	LSO 60-60
LED	High Efficiency Mid-Power LED		
System Power	20 W	27-35-42W	30-40W
Light Flux	2.200 lm	2970-3850-4450lm	3300 - 4350lm
Colour Temperature	3000 - 4000 - 5000 K		
Voltage	220V - 50Hz		
Body	0,60 DKP sheet		
Diffuser	1,2 mm thick opal		
Cooler	Cooling from the body surface		
Frame	1 mm DKP sheet		
Colour	White or Grey		
Box Dimensions	39x39x10 cm	32x122x8 cm	65x64x14 cm
Weight	2.000 gr	5.000 gr	5.100 gr


## Office Lighting

## DARKZONE


IP20



LSR60/3





LSR60/2




LSR60/1

Surface mounted luminaires can be used in many areas such as school, hospital, office, store, hotel etc. Darkzone surface mounted luminaires emerge as an important solution in these areas where glare is a problem. The luminaires do not distort the aesthetics of the spaces with their fine and elegant structure and do not tire the eyes.




Code	LSR60/3	LSR60/2	LSR60/1
LED	High Efficiency Mid-Power LED		
System Power	35 W	45 W	60 W
Light Flux	3.150 lm	4.250 lm	5.850 lm
Colour Temperature	3000 - 4000 - 5000 K		
Voltage	220V - 50Hz		
Body	0,6 mm A1 quality DKP sheet steel 80 micron powder paint		
Optic	Cat-1, Cat-2	Cat-1, Cat-2	Cat-1, Cat-2
Reflector	Polycarbonate		
Cooler	Cooling from the body surface		
Colour	White		



## Office Lighting

# DARKZONE

IP20





LSR30/2



LSR30/1

Designed to be a unique choice in areas where light comfort comes to the forefront, the DarkZone stand out with their simple but elegant stance. The special reflector structures used in the luminaires are designed to provide the best solution for areas where glare is not desired. It minimizes eye fatigue by providing extremely high visibility in an area where glare is virtually absent.



Code	LSR30/2	LSR30/1
LED	High Efficiency Mid-Power LED	
System Power	26 W	13 W
Light Flux	2.900 lm	1.450 lm
Colour Temperature	3000 - 4000 - 5000 K	
Voltage	220V - 50Hz	
Body	0,6 mm A1 quality DKP sheet steel 80 micron powder paint	
Optic	Cat-1, Cat-2	Cat-1, Cat-2
Reflector	Polycarbonate	
Cooler	Cooling from the body surface	
Colour	White	



## Office Lighting

## LSL-P / LSL-OP

IP20




LSL-P



LSL-OP

LSL Series fixtures are surface-mounted fixture with a wide high range of applications. The fixture is produced in different optical structures as double parabolic and opal. The high permeable lens material prevents the decrease of fixture efficiency while eliminating the problem of glare. It enables economic use by mounting to ceiling easily and thanks to the low energy consumption thereof.



Code	LSL-P	LSL-OP
LED	High Efficiency Mid-Power LED	High Efficiency Mid-Power LED
System Power	18 W	14,5 W
Light Flux	2000 lm	1500 lm
Colour Temperature	3000 - 4000 - 5000 K	
Voltage	220V - 50Hz	
Body	0,6 mm thick DKP sheet steel	
Reflector	Alanod Miro Silver (only LSL/P)	
Diffuser	3mm Micro-Prismatic 92% transparent	1,2 mm opal
Cooler	Cooling from the body surface	
Colour	White	
Box Dimensions	42x42x9cm	
Weight	2.800 gr	2.500 gr


## Office Lighting

## FNSS-Y

IP20



FNSS-Y 60




FNSS-Y 40


FNSS-Y 30

FNSS-Y model is a surface-mounted fixture in the form of circle with a stylish look and energy-saving is ensured substantially by virtue of the LED technology used and can be manufactured in various sizes.


FNSS-Y 60



FNSS-Y 40



FNSS-Y 30




Code	a	b
FNSS-Y 30	260 mm	100 mm
FNSS-Y 40	350 mm	100 mm
FNSS-Y 60	550 mm	100 mm

Code	FNSS-Y 30	FNSS-Y 40	FNSS-Y 60
LED	High Efficiency Mid-Power LED		
System Power	20 W	20 / 30 W	40 W
Light Flux	1900 lm	2320/3160 lm	3580 lm
Colour Temperature	3000 - 4000 - 5000 K		
Voltage	220 VAC - 50 Hz		
Body	1,5 mm thick DKP sheet		
Diffuser	1,2 mm thick opal		
Cooler	Cooling from the body surface		
Colour	White		
Box Dimensions	28x28x15 cm	36x36x12 cm	67x61x10 cm
Weight	1.950 gr	3.100 gr	6.550 gr

## Hygienic Room Luminaires


### HFC

IP54



Fixtures with high protection class are produced with specifications to be used in areas where cleaning is important.

Light coming from multi LED source in fixtures passes through a sandblasted specially produced glass, and provides an extremely soft and homogeneous distribution to the environment. Fixture efficiency is brought to the forefront in the clear glass option. It is possible to produce according to all types of suspended ceilings.



	Code	a	b	Cut-Out
<b>MODULAR</b>	HFC 300	595mm	595mm	580x580mm
<b>CLIP-IN</b>	HFC 002	599mm	599mm	-


Code	HFC
LED	High efficiency Mid-Power LED
System Power	40 W
Light Flux	3,750 lm
Colour Temperature	3000-4000-5000 K
Cooler	Cooling from the body surface
Voltage	220V - 50Hz
Body	0,6mm thick A1 quality DKP steel sheet. 80 micron electrostatic powder painted.
Glass	4mm thick tempered glass 1,2mm opal
Colour	White
Box Dimensions	62x62x13cm
Weight	9.000 gr




## Hygienic Room Luminaires

### HFC-SR

IP54



It is presented as a unique solution for hospitals, dentists and laboratories, where the provision of clean room conditions is obligatory in addition to its light distribution prevent glare. Liquid and dust particles that can penetrate into the fixture are prevented by fulfilling the requirements of high protection classes.



	Code	a	b	Cut-Out
<b>MODULAR</b>	HFC 300/SR	595mm	595mm	580x580mm
<b>CLIP-IN</b>	HFC 002/SR	599mm	599mm	-

Code	HFC-SR
LED	High efficiency Mid-Power LED
System Power	27W - 35W
Colour Temperature	3000-4000-5000 K
Cooler	Cooling from the body surface
Voltage	220V - 50Hz
Body	0,6mm thick A1 quality DKP sheet steel. Painted with 80 micron thick electrostatic paint.
Glass	Tempered and transparent glass
Reflector	0,4 mm thick DKP sheet with perforated lens
Colour	White
Box Dimensions	62x62x13cm
Weight	8.000 gr


## Linear Lighting

### DARKLINE

IP20




DLD/BBBBB




DLD/WWWWW


Black and white reflectors are the most successful optical elements in controlled environments where light escape is required and reflector reflections are to be minimized. Office, laboratory and so on. These are the types of luminaires that can be the best solution for environments.




DLD/BBBBB




DLD/WWWWW



DLE/WWWWW



DLE/BBBBB



	DIRECT - Surface or Pendant		DIRECT-INDIRECT - only Pendant	
Code	DLD/BBBBB	DLD/WWWWW	DLE/BBBBB	DLE/WWWWW
LED	High efficiency Mid-Power LED			
System Power	55W	55W	65W	65W
Light Flux	6.100lm	6.100lm	6.700lm	6.700lm
Colour Temperature	3000 - 4000 - 5000 K			
Voltage	220V - 50Hz			
Body	Aluminum extrusion body and painted with electrostatic powder paint.			
Reflector	Polycarbonate			
Colour	White or Grey			
Weight	3.6kg	3.6kg	3.3gr	3.3kg

Note: Suspension apparatus should be requested when used as a pendant.

## Linear Lighting

## DARKLINE

IP20



DLD/BOOOB




DLD/BCCCB


It is a very sensitive issue that the luminaires can be customized in terms of ideal conditions and the luminaires show a harmonious appearance to the decoration. Darkline luminaires easily handle such situations.




DLD/BOOOB




DLD/BCCCB



DLE/BOOOB



DLE/BCCCB




	DIRECT - Surface or Pendant		DIRECT-INDIRECT - Pendant	
Code	DLD/BOOOB	DLD/BCCCB	DLE/BOOOB	DLE/BCCCB
LED	High efficiency Mid-Power LED			
System Power	55W	22W	65W	32W
Light Flux	4.350lm	2.450lm	4.900lm	3.000lm
Colour Temperature	3000 - 4000 - 5000 K			
Voltage	220V - 50Hz			
Body	Aluminum extrusion body and painted with electrostatic powder paint.			
Reflector	Polycarbonate			
Colour	White or Grey			
Weight	3.6kg	3.6kg	3.3gr	3.3kg

Note: Suspension apparatus should be requested when used as a pendant.


## Linear Lighting

## DARKLINE

IP20



DLD/WOOOW




DLD/WCCCW


It is a very sensitive issue that the luminaires can be customized in terms of ideal conditions and the luminaires show a harmonious appearance to the decoration. Darkline luminaires easily handle such situations.




DLD/B000B




DLD/BCCCB



DLE/B000B



DLE/BCCCB



	DIRECT - Surface or Pendant		DIRECT-INDIRECT - Pendant	
Code	DLD/WOOOW	DLD/WCCCW	DLE/WOOOW	DLE/WCCCW
LED	High efficiency Mid-Power LED			
System Power	55W	22W	65W	32W
Light Flux	4.350lm	2.450lm	4.900lm	3.000lm
Colour Temperature	3000 - 4000 - 5000 K			
Voltage	220V - 50Hz			
Body	Aluminum extrusion body and painted with electrostatic powder paint.			
Reflector	Polycarbonate			
Colour	White or Grey			
Weight	3.6kg	3.6kg	3.3kg	3.3kg


Note: Suspension apparatus should be requested when used as a pendant.



## Linear Lighting

### DARKLINE

IP20




DLD/O


Optimal solution is to use luminaires with opal diffusers to softly distribute light in environments. Depending on the color temperature to be used in the luminaires, the effect and feeling can be created as desired in the spaces.



DLD/O



DLE/O




Code	DLD/O	DLE/O
LED	High efficiency Mid-Power LED	
System Power	35W	50W
Light Flux	2.470lm	3.650lm
Colour Temperature	3000 - 4000 - 5000 K	
Voltage	220V - 50Hz	
Body	Aluminum extrusion body and painted with electrostatic powder paint.	
Diffuser	Opal - microprismatic	
Colour	White or Grey	
Weight	3.6kg	3.3kg

## Linear Lighting

### EOSLED

IP20  
IP40 Optional

DFR fixtures which can be used as surface mounted and pendant are produced in 19 - 60 - 80mm width. They can be used as a single profile up to approximately 2.5 meters length in linear applications. They can be attached end to end and be used as a continuous light source. Height of the pendant can be easily adjusted thanks to spring mounting parts.



DFR 20



DFR 60




DFR 80



Code	a	b	c
DFR 20/100	1024mm	19mm	16mm
DFR 20/120	1194mm	19mm	16mm
DFR 20/150	1528mm	19mm	16mm
DFR 60/100	1024mm	60mm	90mm
DFR 60/120	1194mm	60mm	90mm
DFR 60/150	1528mm	60mm	90mm
DFR 80/100	1024mm	80mm	85mm
DFR 80/120	1194mm	80mm	85mm
DFR 80/150	1528mm	80mm	85mm



DFR BP



DFR AT




DFR SP1



DFR SP2

DFR 60 - 80




Code	DFR 20/20 DFR 20/50 DFR 20/100	DFR 60/100 DFR 60/120 DFR 60/150	DFR 80/100 DFR 80/120 DFR 80/150
LED	High efficiency Mid-Power LED		
System Power	2.5 W 7.5 W 15 W	35 W 35 W 45 W	30 W 35 W 45 W
Light Flux	220 lm 660 lm 1.250 lm	3.200 lm 3.200 lm 4.000 lm	2.800 lm 3.200 lm 4.000 lm
Colour Temperature	3000 - 4000 - 5000 K		
Voltage	220V - 50Hz		
Body	Aluminum extrusion body 80 micron electrostatic powder coated with paint.		
Diffuser	Prismatic Opal		
Colour	White or Grey		
Weight	500 gr 600 gr 750 gr	3000 gr 3750 gr 4500 gr	3400 gr 4100 gr 5200 gr

## Linear Lighting

### EOSLED

### IP20 IP40 Optional


DFG fixture series, which are the recessed type of EOSLED are produced in different widths. They can be used as a single profile up to approximately 2.5 meters length in linear applications. They can be attached end to end and be used as a continuous light source. Puller ceiling mounting device has been used in order to adhere to the surface of the edge of the frame thoroughly on the ceiling. Light coming from the LED source creates an extremely soft ambiance by passing through the micro-prismatic diffusers.



DFG 20



DFG 50



DFG 80




Code	a	b	c
DFG 20/100	1038mm	35mm	16mm
DFG 20/120	1208mm	35mm	16mm
DFG 20/150	1542mm	35mm	16mm
DFG 50/100	1036mm	73mm	83mm
DFG 50/120	1236mm	73mm	83mm
DFG 50/150	1536mm	73mm	83mm
DFG 80/100	1034mm	95mm	85mm
DFG 80/120	1204mm	95mm	85mm
DFG 80/150	1538mm	95mm	85mm



DFG BP

Code	DFG 20/20 DFG 20/50 DFG 20/100	DFG 50/100 DFG 50/120 DFG 50/150	DFG 80/100 DFG 80/120 DFG 80/150
LED	High efficiency Mid-Power LED		
System Power	2.5 W 7.5 W 15 W	30 W 35 W 45 W	30 W 35 W 45 W
Light Flux	220 lm 660 lm 1.250 lm	2.300 lm 2.600 lm 3.400lm	2.800 lm 3.300 lm 4.000 lm
Colour Temperature	3000 - 4000 - 5000 K		
Voltage	220V - 50Hz		
Body	Aluminum extrusion body 80 micron electrostatic powder coated with paint.		
Diffuser	Prismatic Opal		
Colour	White or Grey		
Weight	500 gr 600 gr 750 gr	1.900 gr 2.300 gr 2.700 gr	3.400 gr 4.100 gr 5.200 gr

DFG 80




## Linear Lighting

DLG

IP20



DLG/B BBBB



DLG/W WWWW

Black and white reflectors are the most successful optical elements in controlled environments where light escape is required and reflector reflections are to be minimized. Office, laboratory and so on. These are the types of luminaires that can be the best solution for environments.

DLG/B or DLG/W



DLG/BB or DLG/WW





DLG/BBB or DLG/WWW




DLG/B BBBB or DLG/W WWWW




DLG/B BBBB or DLG/W WWWW



DLG/B BBBB



DLG/W WWWW




Code	DLG/B BBBB	DLG/W WWWW
LED	High efficiency Mid-Power LED	
System Power	55W	55W
Light Flux	6.100lm	6.100lm
Colour Temperature	3000 - 4000 - 5000 K	
Voltage	220V - 50Hz	
Body	Aluminum extrusion body and painted with electrostatic powder paint.	
Optic	CAT1 - CAT2	
Diffuser	Polycarbonate	
Colour	White or Grey	
Weight	2.2kg	



## Linear Lighting


### DFR40

IP20




Connector for linear application

The DFR 40 is a type of luminaire suitable for various places with its slim, elegant appearance and ease of use. It is an economic model thanks to its simple design. The luminaire can be easily assembled. The connection cable does not disturb the luminaire image because it passes through the middle of the luminaire. Independent and linear applications are among the features of this luminaire.



Code	a
DFR40/60	560 mm
DFR40/120	1.100 mm



Code	DFR40/60	DFR40/120
LED	Midpower Led	
System Power	17 W	34 W
Light Flux	1350 lm	2640lm
Colour Temperature	3000-4000-5000 K	
Voltage	220V - 50Hz	
Body	Aluminum extrusion	
Diffuser	Opal - Acrylic diffuser	
Colour	White	

## Decorative Luminaires

## SLO

IP20



SLO luminaires are very wide range of luminaires. The circular structure of the luminaire reveals a unique mood in the room. The snap-on mechanism, which can be adjusted in height, provides great convenience in installation. The array of LEDs integrates with the opal diffuser to provide extremely soft light distribution. In terms of being able to adapt to the environment, they are presented in black and white colors.

SLO60 600mm 114mm

SLO90 900mm 114mm

SLO120 1200mm 114mm


Code	SLO 60	SLO 90	SLO 120
LED	High efficient Mid-Power LED		
System Power	30 W	45 W	60 W
Colour Temperature	3000 - 4000 - 5000 - 6500 K		
Voltage	220V - 50Hz		
Body	Aluminum		
Diffuser	Opal lens		
Colour	Black - White		
Accessory	Pendant apparatus		
Box Dimensions	62x62x16cm	92x92x16cm	122x122x16

## Decorative Luminaires

## BLOOM

IP20

They can be used single while it is possible to create quite different shapes by using side by side and in multi usage. It can be used alone together as using multiple. What a designer can achieve is only limited to his own imagination with multiple usages of color options. They are designed for use in wall and ceiling surfaces. The aesthetic effect it creates on the surface even when the fixtures are deactivated reflects the unique design approach thereof.





Code	BLM 30	BLM 60
LED	High efficiency Mid-Power LED	
System Power	15 W	27 W
Light Flux	1,600 lm	2,700 lm
Colour Temperature	2700-3000-4000-5000K, R-G-B	
Voltage	220V - 50Hz	
Body	Manufactured from DKP sheet steel	
Diffuser	Opal	
Cooler	Cooling from the body surface	
Colour	Optional - RAL colour	
Box Dimensions	31x31x6cm	61x61x6cm
Weight	2.800 gr	4.800 gr

## Wall Luminaires

## DAP

IP40

Highly energy efficient DAP can be used in many areas of architecture thanks to its aesthetic wall mounting apparatus. It can be preferred as unidirectional and bidirectional according to the features of the area to be illuminated. LED lamps which can provide narrow and wide angle light can create the desired effect on the surface.



Code	DAP 15	DAP 25
LED	Par 16 Led lamp	
System Power	1x5 W	2x5 W
Colour Temperature	3000 - 4000 - 5000 K	
Voltage	220V - 50Hz	
Body	2.5 mm thick aluminum extrusion, epoxy polyester powder paint	
Colour	Grey	
Box Dimensions	21x22x16,5 cm	
Weight	1.450 gr	






## Wall Luminaires

## MDW

Up&amp;Downside IP65

Downside IP40

MDW brings distinction to the surrounding with its unusual design and advanced technology for both indoor and outdoor lighting applications. Besides combining light efficiency and comfort, this model offers another distinctive feature. It creates a mystic ambiance integrated with the architecture. With its up, down and up/down variations, architectural details on the surface are illuminated with soft light.



Code	MDW 113	MDW 213
LED	High efficiency COB LED	
System Power	1x13 W	2x13 W
Light Flux	1.170 lm	2.340 lm
Colour Temperature	3000 - 4000 - 5000 K	
Voltage	220V - 50Hz	
Body	3 mm thick aluminum extrusion	
Reflector	1 mm thick 99.9% pure aluminum	
Glass	5 mm tempered glass	
Colour	Grey	
Box Dimensions	30x44x22 cm	
Weight	7.000 gr	

## Wall Luminaires


### WLS



IP44



WLS coded products are wall luminaires that can provide double-sided light. They can be used horizontally or vertically. It is possible to make creative lighting designs when used together in different sizes and mixing long size and short size together. It can be used linearly especially in hall areas.

The luminaires can be easily mounted with the claw mounting brackets.



		
Code	WLS100-2	WLS100-1
LED	High efficiency Midpower LED	
Power	34W	17W
Luminous Flux	2.200lm	1.100lm
Colour Temperature	3000 - 4000 - 5000K	
Voltage	220V - 50Hz	
Body	Aluminum extrusion	
Cooler	Aluminum	
Diffuser	Acrylic opal lens	

## Over Mirror Luminaires

### LML

IP44



The LML luminaires have a stylish and aesthetic sense with the ease of installation. Thanks to the opal diffuser, which has a high light output and a homogeneous light distribution, it prevents glare in over mirror use. The chrome-plated end caps provide adequate protection against ambient conditions. The luminaires are manufactured in a manner to be suitable for wall and ceiling use.



600mm



65mm

53mm

Code	LML60/10	LML60/16	LML60/20
LED	High efficiency Midpower LED		
Power	10W	16W	20W
Luminous Flux	1.000lm	1.600lm	2.050lm
Colour Temperature	3000-4000-5000K		
Voltage	220V - 50Hz		
Body	Aluminum extrusion - ABS material end caps are chrome coated		
Cooler	Aluminum		
Diffuser	Acrylic opal lens		


## Industrial Lighting

## ENDILED - High Efficiency


IP66

Optional  
LBS/OP IP20


ENDILED luminaires are high protection class aluminum bodied fixtures produced with extremely high technology. They are suitable for use in many areas of industry, such as production areas, storage areas and particularly in high-ceilinged places. Reflectors produced with 98% optical efficiency by Alanod Miro-Silver technology are used in fixtures in order to ensure high efficiency. Heating problems are completely solved thanks to the aluminum body and PCB with high thermal conductivity aluminum.




Narrow Angle



Medium Angle



Wide Angle



Code	a
LBS 6	796 mm
LBS 9	796 mm
LBS 12	1.396 mm
LBS 20	1.396 mm

Code	LBS 6	LBS 9	LBS 12	LBS 20
LED	High efficiency Mid-Power LED			
System Power	40 W	60 W	80 W	130 W
Light Flux	6.000 lm	8.800 lm	11.900 lm	20.400 lm
Colour Temperature	3.000 - 4.000 - 5.000 - 6.500 K			
Driver	Osram			
Voltage	220 volt - 50hz			
Body	Aluminum extrusion body, end caps are aluminum injection			
Cooler	Aluminum special body structure ensuring quick heat transfer			
Reflector	Miro Silver 4: Bright narrow Miro Silver 5: Matt medium - wide			
Diffuser	Tempered glass or protective film Acrylic prismatic diffuser for soft applications. (IP20)			
Colour	Eloxal matt			
Box Dimensions	72x11x12cm		132x11x12cm	



## Industrial Lighting

**100.000hrs**  
**Lifetime**

# ENDILED - Longlife


**IP66**


LBS Longlife Luminaires are industrial type luminaires that can be used in areas where replacement is difficult. They are luminaires that can be used without needing to change for a long time.


The special type, long life and high efficiency driver / LED are used in these Luminaires and therefore the life time of the luminaires is maximized.

The body of the luminaire is made of aluminum extrusion material and end caps are manufactured by aluminum injection.


The optical elements used in the luminaires have been developed to offer 3 different options depending on the height of the ceiling: narrow, medium and wide angle.




Narrow Angle




Medium Angle



Wide Angle



Code	LBS LL
LED	High efficiency Mid-Power LED
System Power	148 W
Light Flux	14.700 lm
Colour Temperature	3.000 - 4.000 - 5.000 - 6.500 K
Driver	Tridonic Pro - 200.000Hrs lifetime
Voltage	220 volt - 50hz
Body	Aluminum extrusion body, end caps are aluminum injection
Cooler	Aluminum special body structure ensuring quick heat transfer
Reflector	Miro Silver 4: Bright narrow - medium - wide Miro Silver 5: Matt narrow - medium - wide
Diffuser	Tempered glass or protective film
Colour	Eloxal matt
Box Dimensions	142x11x12cm




## Industrial Lighting

### TEKNOMAX

IP66


TEKNOMAX luminaires are designed for operating without any problems in industrial locations where luminaire bodies are exposed to harsh environment conditions. The luminous efficiency of the luminaires has been reached to extremely high levels. The luminaire efficiency comes from combining the optic design with the newest generation LEDs in the most appropriate way. Narrow and wide angle types of luminaires can be produced according to ceiling heights. Luminaires can be installed in any way using busbar, cable tanks and free hangers.



#### Brackets




HCL-YT/AB  
Busbar





HCL-YT/AK  
Cable Tray




HCL-YT/AG  
Free bracket




HCL-YT/AS



#### Narrow Angle



#### Wide Angle



Code	HCL-YT 50	HCL-YT 100	HCL-YT 150	HCL-YT 200	HCL-YT 240
LED	High efficiency Mid-Power LED				
System Power	50W	100W	150W	200W	240W
Light Flux	7.000lm	13.000lm	19.500 lm	25.000 lm	30.000 lm
Colour Temperature	3000 - 4000 - 5000 K				
Voltage	220V - 50Hz				
Body	Aluminum injection				
Reflector	Alanod Miro Silver aluminum				
Diffuser	Impact resistance tempered glass with serigraphy printed				
Colour	Grey				
Weight	13.000 gr				

## Industrial Lighting

## TERMOMAX



IP66



**+90°C**  
Ambient  
Temperature

Heavy industrial processes are carried out in industrial plants and industrial lighting must be designed and applied to these facilities to withstand harsh environmental conditions such as high temperature and humidity. TERMOMAX luminaires are designed with high efficiency and the ability to work without any problem at +90°C temperature in industrial plants.

The possibility of offering high performance solutions from the point of view of energy saving and offering a long-lasting system has made TERMOMAX one of the most competitive and future-proof technology in the industrial lighting sector. TERMOMAX luminaires produced with LEDs with long life and high efficiency have high light distribution levels with low energy levels.



Code	HCL-TM
LED	High Power - Cree XHP70
System Power	70 W
Light Flux	8.560 lm
Operating Temperature	- 40° C ~ +90° C
Colour Temperature	3000 - 4000 - 5000 K
Voltage	220V - 50Hz
Body	Aluminum injection
Diffuser	Impact resistance tempered glass with serigraphy printed
Reflector	Ledil Minnie Reflector
Colour	Grey
Weight	12.000 gr


Weatherproof

## ELP

IP65



Code	a
ELP60	630 mm
ELP120	1230 mm



Code	ELP60-18	ELP120-35	ELP120-58
LED	High efficiency Mid-Power LED		
System Power	18W	35W	58W
Light Flux	1.850lm	3.780lm	5.800lm
Colour Temperature	3.000 - 4.000 - 5.000 K		
Voltage	220 volt - 50hz		
Body	Plastic extrusion polycarbonate, end caps are ABS		
Cooler	Aluminum extrusion		
Diffuser	Polycarbonate		
Colour	White - Gray		
Accessories	Stainless mounting clips		
Weight	1.160gr (ELP120)		



Weatherproof

ELP/M


IP65



The ELP/M waterproof fixtures have high protection class aluminum extrusion body against water and dust with LED light source. They can be used in many areas such as parking lots, storage areas and other areas for industrial purposes. They provide extra energy savings by reducing the light when it is not needed thanks to their suitability for automation.



Code	a
ELP/M60	630 mm
ELP/M120	1230 mm



Code	ELP/M60-18	ELP/M120-35	ELP/M120-58
LED	High efficiency Mid-Power LED		
System Power	18W	35W	58W
Light Flux	1.850lm	3.860lm	5.900lm
Colour Temperature	3.000 - 4.000 - 5.000 K		
Voltage	220 volt - 50hz		
Body	Aluminum extrusion end caps are ABS		
Cooler	Aluminum extrusion		
Diffuser	Polycarbonate		
Colour	Eloxal body, end caps are gray		
Accessories	Stainless mounting clips		

Weatherproof

## ELW

IP65

They can be used in many areas for parking, storage, technical rooms and other areas for industrial purposes. It is possible to reduce and increase the light level by controlling with the automation system. While saving energy in this way, the luminaire life does not decrease thanks to the LEDs used in the product.



Suspension System


(Driver On Board)



IP65 Driver Type



90 mm



Code	ELW120-40	ELW120-60	ELW120-80
LED	High efficiency Mid-Power LED		
System Power	40 W	60 W	80 W
Light Flux	4.400lm	6.600lm	8.800lm
Colour Temperature	3000 - 4000 - 5000 - 6500 K		
Cooler	Cooling from the body surface		
Voltage	220 volt - 50hz		
Body	Aluminum extrusion		
Diffuser	Opal - Polycarbonate diffuser		
Colour	Matt anodized		
Accessory	Assembly springs		
Box Dimensions	17x132x12 cm		
Weight	3.100 gr		




## Emergency Lighting

LXT

IP40



Litpa emergency exit and steering luminaire is a reliable luminaire option with high quality material structure and technical specifications. Suitable for single face and double face use. Suitable for many areas of use, from offices to meeting rooms, shopping centers to schools.



Code	LXT
Environment	Wall and Ceiling Surface
LED	Midpower LED
Power	3W
Light Flux	95lm
Charging Time	24 hrs
Decharging Time	3 hrs
Working Temperature	-5°C + 45°C
Class	I
Battery	1.2Vdc 1000mAh durable Ni-Cd
Diffuser	Plexiglass
Colour Temperature	6000 K
Voltage	220 volt - 50hz
Görülebilirlik	15 - 30m

## Linear Lighting

### TRL



The TRL trunking system can be inserted end-to-end in a linear manner. Trunking lengths can be made in different lengths from 1.5 meters to 4.5 meters. The joining members firmly secure the channel modules together. Various mounting parts that can be used in different pans or hanger systems allow easy installation without any problems.

#### Body:

It is produced by aluminum extrusion method. At least 80 micron thick electrostatic powder painted. U-shaped design and strength-enhancing folds keep the stretch of the linear trunking at a minimum and prevent sagging aesthetics.

#### Properties:

The contractors on the cable gates inside the trunking allow phase selection using the adjustable terminals from the top cover of the LED modules. 5-wire and 7-wire systems are available. In the 5-wire system, it carries 3 phases, neutral and ground lines within the trunking. The user can choose between 3 phases. In 7-wire system, it carries 3-phase, neutral and earth lines and also carries 2 cables. These cables are used as DALI automation line. Here again, phase selection is made and the data is transferred to the fixture module from 2 points.



TRL5

TRL7



Code	Length	LxWxH
TRL5/150	Single Length (1x)	1.500x68x55 mm
TRL5/300	Double Length (2x)	3.000x68x55 mm
TRL5/450	Triple Length (3x)	4.500x68x55 mm
TRL7/150	Single Length (1x)	1.500x68x55 mm
TRL7/300	Double Length (2x)	3.000x68x55 mm
TRL7/450	Triple Length (3x)	4.500x68x55 mm

CHA



Chain hanger

TWA



Suspension bracket

FRA



Free suspension

TCN

Canal connection  
apparatus

CAP



End Cap

CTR



Cable canal



## Linear Lighting

### TCR

IP20




TCR is a highly efficient fixture series developed to apply LED technology in lighting of supermarkets, hobby stores, electronics stores as well as production areas that do not require high protection class such as warehouses, hangars and other interior spaces. The light coming from the LED light source is directed to usage areas with high efficiency in fixtures. It creates an extremely comfortable, refreshing and not disturbing environment due to both the quality of light and to low dazzling feature of the light directed from the prismatic diffusers.



### Trunking System



Luminaires can be produced according to the trunking system.



TRL canal can be easily installed by pressing the lock on the luminaire body with the finger.



Code	TCR 35	TCR 50
LED	High efficiency Mid-Power LED	
System Power	35W	50W
Light Flux	3.300 lm	4.750 lm
Colour Temperature	3000 - 4000 - 5000 K	
Driver	Osram, Tridonic or Helvar	
Voltage	220V - 50Hz	
Body - Reflector	0,6 mm thick DKP sheet steel	
Diffuser	Prismatic lens	
Cooler	Cooling from the body surface	
Colour	White	
Accessory	Pendant, connection apparatus, end-cap	
Box Dimensions	12x15x152cm	
Weight	4.000 gr	

## Linear Lighting

### TCA


IP20




Tekholine TCA coded products provide high luminous efficiency in many areas. Both lens and LED quality and efficiency are the highest in the products. The fixture body integrates with the aluminum extrusion material and provides adequate and uniform cooling.

There is a separate optical chamber for each LED. In this way, the light coming out of the leds is controlled with every direction, while the glare is minimized.

### Trunking System



TRL canal can be easily installed by pressing the lock on the luminaire body with the finger.



Code	TCA150HE		TCA150HO	
LED	High efficiency Mid-Power LED			
System Power	43W		65W	
Light Flux	5.010lm	Medium Beam	6.730lm	Medium Beam
	4.990lm	Wide Beam	6.710lm	Wide Beam
	4.840lm	Asymmetrical	6.540lm	Asymmetrical
	4.970lm	Double Asym.	6.680lm	Double Asym.
Colour Temperature	3000 - 4000 - 5000 - 6.500K			
Voltage	220V - 50Hz			
Body	Aluminum extrusion			
Diffuser	Vossloh Schwabe or Ledil lens			
Cooler	Cooling from the body surface			
Colour	White			
Box Dlmension	162x18x13cm)			
Weight	6.4kg (4pcs in box)			

## Linear Lighting

### TCE



IP20





Teknoline TCE products provide high luminous efficiency in many areas. Both lens and LED quality and efficiency are the highest in the products. The fixture body integrates with the aluminum extrusion material and provides adequate and uniform cooling.

There is a separate optical chamber for each LED. In this way, the light coming out of the leds is controlled with every direction, while the glare is minimized.

### Trunking System



TRL canal can be easily installed by pressing the lock on the luminaire body with the finger.



Code	TCE150HE		TCE150HO	
LED	High efficiency Mid-Power LED			
System Power	44W		62W	
Light Flux	5.990lm	Narrow Beam	7.810lm	Narrow Beam
	6.030lm	Wide Beam	7.830lm	Wide Beam
	5.910lm	Very Wide Beam	7.650lm	Very Wide Beam
	5.900lm	Asymmetrical	7.670lm	Asymmetrical
	6.040lm	Double Asym.	7.820lm	Double Asym.
Colour Temperature	3000 - 4000 - 5000 - 6.500K			
Voltage	220V - 50Hz			
Body	Aluminum extrusion			
Diffuser	Vossloh Schwabe or Ledil lens			
Cooler	Cooling from the body surface			
Colour	White			
Box Dlmension	162x18x13cm)			
Weight	7.5kg (4pcs in box)			



# INDEX

<b>B</b>	
BLM.....	67
BOLLARD.....	19
BLOOM.....	67

<b>C</b>	
CAIRO.....	6
CRA.....	6

<b>D</b>	
DAP.....	68
DARKLINE.....	58
DARKZONE.....	44-52
DFG.....	63
DFR.....	62
DFR40.....	65
DLD.....	58
DLE.....	58-61
D-LFB.....	21
D-LFK.....	21
DLG.....	64
D-LSD.....	21
D-LYD.....	21
DML.....	30
DOT.....	35
DR.....	34

<b>E</b>	
ELD.....	36
ELP.....	76
ELP/M.....	77
ELW.....	78
ENDILED.....	72
EOSLED.....	62

<b>F</b>	
FASHIONLED.....	28
FNSB-K.....	48
FNSB-Y.....	49
FNSS-Y.....	55

<b>G</b>	
GALAXYLED.....	31

<b>H</b>	
HADES.....	16
HERCULED.....	8-9
HCL.....	8-9
HCL-T.....	23
HCL-TM.....	75
HCL-YT.....	74
HFC.....	56
HFC-SR.....	57
HRN.....	37
HYL.....	16

<b>L</b>	
LBS.....	72
LBS LL.....	73
LDD.....	15
LEG-OP.....	46
LEG-PR.....	46
LGO.....	43
LGR.....	44
LGS.....	42
LKG.....	38
LML.....	71
LSH.....	20
LSL-OP.....	54
LSL-P.....	54
LSO.....	51
LSR.....	62
LSS.....	50
LYS.....	4
L1671.....	37
LUXOR.....	19
LXT.....	79

<b>M</b>	
MDL.....	10
MDW.....	69
MOON.....	47
MSG.....	27a
MSH.....	18

<b>O</b>	
OFISLED.....	42
OLG.....	47

<b>P</b>	
PETROLED.....	20
PGH.....	35
PGR.....	45
PNS.....	41
PTL.....	22
PUNTO.....	27

<b>Q</b>	
QUANTUM.....	12-13
QTM.....	12-13

<b>R</b>	
RINGA.....	5
RLP.....	28
RLP/S.....	41
RLK.....	28
RLK/M.....	29
RNY.....	5
RTL.....	11

<b>S</b>	
SCP.....	40
SFR.....	32
SHOPLED.....	26
SHOWLED.....	30
SLG.....	26
SLK.....	41
SLO.....	66
SLY.....	41
SMG/L.....	33
SSL.....	27
STREETRAY.....	4

<b>T</b>	
TEKNOLINE.....	80
TEKNOMAX.....	74
TERMOMAX.....	75
TCA.....	82
TCE.....	83
TCR.....	81
TRL.....	80

<b>Y</b>	
YLW.....	17

3007.....	19
8040.....	19
8050.....	19