

Office Lighting

LEG-PR / LEG-OP

IP20


Glare and screen reflections have been taken into consideration in the optical design of the LEG series fixtures which are direct-indirect fixtures which are the most important requirements in offices. The fixture has been developed in direct - indirect mixed optical structure according to Cat-1 and Cat-2 types. The fixture is produced in different optical structures as double parabolic and opal. It is designed to be used in a suitable way in any office perfectly.



LEG-PR



LEG-OP



	Code	a	b	Cut-Out
System Ceiling	LEG-PR 001	595mm	595mm	580x580mm
	LEG-OP 001	595mm	595mm	580x580mm
Clip-in	LEG-PR 002	599mm	599mm	-
	LEG-OP 002	599mm	599mm	-
Modular	LEG-PR 300	595mm	595mm	-
	LEG-OP 300	595mm	595mm	-

Code	LEG-PR	LEG-OP
LED	High Efficiency Mid-Power LED	
System Power	26 - 35 W	26 - 37 W
Light Flux	1700 - 2280lm	1490 - 2120 lm
Colour Temperature	3000 - 4000 - 5000 K	
Driver	Osram or Tridonic	
Voltage	220V - 50Hz	
Body	6114, A1 quality DKP sheet steel	
Reflector	0,4 mm thickness aluminum	
Cooler	Cooling from the body surface	
Colour	White	
Box Dimensions	61x67x12 cm	61x67x12 cm
Weight	4.900 gr	5.100 gr

