


Linear Lighting

EOSLED


IP20
IP40 Optional



DFG 20



DFG 50



DFG 80

DFG fixture series, which are the recessed type of EOSLED are produced in different widths. They can be used as a single profile up to approximately 2.5 meters length in linear applications. They can be attached end to end and be used as a continuous light source. Puller ceiling mounting device has been used in order to adhere to the surface of the edge of the frame thoroughly on the ceiling. Light coming from the LED source creates an extremely soft ambiance by passing through the micro-prismatic diffusers.



| Code | a | b | c |
|------------|--------|------|------|
| DFG 20/100 | 1038mm | 35mm | 16mm |
| DFG 20/120 | 1208mm | 35mm | 16mm |
| DFG 20/150 | 1542mm | 35mm | 16mm |
| DFG 50/100 | 1036mm | 73mm | 83mm |
| DFG 50/120 | 1236mm | 73mm | 83mm |
| DFG 50/150 | 1536mm | 73mm | 83mm |
| DFG 80/100 | 1034mm | 95mm | 85mm |
| DFG 80/120 | 1204mm | 95mm | 85mm |
| DFG 80/150 | 1538mm | 95mm | 85mm |



DFG BP

| Code | DFG 20/20 DFG 20/50 DFG 20/100 | DFG 50/100 DFG 50/120 DFG 50/150 | DFG 80/100 DFG 80/120 DFG 80/150 |
|--------------------|---|--|--|
| LED | High efficiency Mid-Power LED | | |
| System Power | 2.5 W 7.5 W 15 W | 30 W 35 W 45 W | 30 W 35 W 45 W |
| Light Flux | 220 lm 660 lm 1.250 lm | 2.300 lm 2.600 lm 3.400lm | 2.800 lm 3.300 lm 4.000 lm |
| Colour Temperature | 3000 - 4000 - 5000 K | | |
| Voltage | 220V - 50Hz | | |
| Body | Aluminum extrusion body 80 micron electrostatic powder coated with paint. | | |
| Diffuser | Prismatic Opal | | |
| Colour | White or Grey | | |
| Weight | 500 gr 600 gr 750 gr | 1.900 gr 2.300 gr 2.700 gr | 3.400 gr 4.100 gr 5.200 gr |

DFG 80

