


# Linear Lighting

## EOSLED

IP20  
IP40 Optional

DFR fixtures which can be used as surface mounted and pendant are produced in 19 - 60 - 80mm width. They can be used as a single profile up to approximately 2.5 meters length in linear applications. They can be attached end to end and be used as a continuous light source. Height of the pendant can be easily adjusted thanks to spring mounting parts.



DFR 20



DFR 60




DFR 80



Code	a	b	c
DFR 20/100	1024mm	19mm	16mm
DFR 20/120	1194mm	19mm	16mm
DFR 20/150	1528mm	19mm	16mm
DFR 60/100	1024mm	60mm	90mm
DFR 60/120	1194mm	60mm	90mm
DFR 60/150	1528mm	60mm	90mm
DFR 80/100	1024mm	80mm	85mm
DFR 80/120	1194mm	80mm	85mm
DFR 80/150	1528mm	80mm	85mm



DFR BP



DFR AT




DFR SP1



DFR SP2

DFR 60 - 80



Code	DFR 20/20 DFR 20/50 DFR 20/100	DFR 60/100 DFR 60/120 DFR 60/150	DFR 80/100 DFR 80/120 DFR 80/150
LED	High efficiency Mid-Power LED		
System Power	2.5 W 7.5 W 15 W	35 W 35 W 45 W	30 W 35 W 45 W
Light Flux	220 lm 660 lm 1.250 lm	3.200 lm 3.200 lm 4.000 lm	2.800 lm 3.200 lm 4.000 lm
Colour Temperature	3000 - 4000 - 5000 K		
Voltage	220V - 50Hz		
Body	Aluminum extrusion body 80 micron electrostatic powder coated with paint.		
Diffuser	Prismatic Opal		
Colour	White or Grey		
Weight	500 gr 600 gr 750 gr	3000 gr 3750 gr 4500 gr	3400 gr 4100 gr 5200 gr